

Form PTO-1390

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICEATTORNEY'S DOCKET NUMBER
P20453TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/720250

INTERNATIONAL APPLICATION NO.

PCT/JP99/03802

INTERNATIONAL FILING DATE

14 July 1999

PRIORITY DATE CLAIMED

15 July 1998

TITLE OF INVENTION

MARKETING SUPPORTING SYSTEM

APPLICANT(S) FOR DO/EO/US

Masanori NANBU, Toshio TAMURA, Kohji IWAMOTO, and Yukio FUKUI

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information.

1. ☒ This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)).
4. ☒ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3))
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (U.S.C. 371(c)(5)).

Items 11 to 16 below concern other document(s) or information included:

11. ☐ Assignee: AMADA COMPANY LIMITED
12. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
13. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
14. ☒ A FIRST preliminary amendment.
15. ☐ A SECOND or SUBSEQUENT preliminary amendment.
16. ☐ A substitute specification.
17. ☒ A change of power of attorney and/or address letter.
18. ☒ Figure of Drawing to be published 1
19. ☒ Other items or information:
 - International Application as published Cover Sheet(in Japanese).
 - PCT/PEA/401(in Japanese).
 - PCT/PEA/402(in Japanese).
 - PCT/PEA/409-International Preliminary Examination Report.
 - PCT/IB/338.
 - PCT/IB/308.
 - PCT/ISA/210-International Search Report(in Japanese).
 - Claim of Priority.

U.S. APPLICATION NO: (if known, see 37 CFR 1.5)

09/720250

INTERNATIONAL APPLICATION NO.

PCT/JP99/03802

ATTORNEY'S DOCKET NUMBER

P20453

19. The following fees are submitted:

CALCULATIONS

PTO USE ONLY

Basic National Fee (37 CFR 1.492(a)(1)-(5)):

Search report has been prepared by the EPO or JPO. \$ 860.00

International preliminary examination fee paid to USPTO (37 CFR 1.482). \$ 690.00

No international preliminary examination fee paid to USPTO (37 CFR 1.482) but
international search fee paid to USPTO(37 CFR 1.445(a)(2)). \$ 710.00Neither international preliminary examination fee (37 CFR 1.482) nor
international search fee (37 CFR 1.445(a)(2) paid to USPTO. \$1,000.00International preliminary examination fee paid to USPTO (37 CFR 1.482) and all
claims satisfied provisions of PCT Article 33(2)-(4). \$ 100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

\$860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ___ 20 ___ 30
months from the earliest claimed priority date (37 CFR 1.492(e)).

\$

Claims	Number Filed	Number Extra	RATE		
Total Claims	42 - 20 =	22	X \$18.00	\$396.00	
Independent Claims	11 - 3 =	8	X \$80.00	\$640.00	
Multiple dependent claim(s) (if applicable)			+ \$270.00	\$0.00	

TOTAL OF ABOVE CALCULATIONS =

\$1896.00

Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced
by 1/2.

\$

SUBTOTAL =

\$1896.00

Processing fee of \$130.00 for furnishing the English translation later than ___ 20 ___ 30
months from the earliest claimed priority date (37 CFR 1.492(f)).

+

TOTAL NATIONAL FEE =

\$1896.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

+

\$40.00

TOTAL FEES ENCLOSED =

\$1936.00

Amount to be
refunded

\$

Charged

\$

a. ☒ A check in the amount of \$1936.00 to cover the above fees is enclosed.b. ☐ Please charge my Deposit Account No. _____ in the amount of \$_____ to cover the above fees.c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to
Deposit Account No. 19-0089.NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and
granted to restore the application to pending status.SEND ALL CORRESPONDENCE TO CUSTOMER NO. 7055
AT THE PRESENT ADDRESS OF:Bruce H. Bernstein
GREENBLUM & BERNSTEIN, P.L.C.
1941 Roland Clarke Place
Reston, VA 20191
(703) 716-1191

SIGNATURE

Bruce H. Bernstein

NAME

29,027

REGISTRATION NUMBER

P20453.A01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Masanori NANBU et al.
Serial No : Not Yet Assigned (National Stage of PCT/JP99/03802)
Filed : Concurrently Herewith
For : MARKETING SUPPORTING SYSTEM

PRELIMINARY AMENDMENT

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Prior to calculation of the filing fees and the examination of the above-identified patent application on the merits, the Examiner is respectfully requested to amend the claims as follows:

IN THE CLAIMS

Please amend the claims as follows:

Claim 28, line 2, delete "or 27".

Claim 34, line 2, delete "or 33".

Claim 35, line 2, change "any one of claims 31 to 34" to ---claim 31---.

Claim 36, line 2, change "any one of claims 31 to 34" to ---claim 31---.

Claim 39, line 2, delete "or 38".

Claim 42, lines 3 and 4, change "claims 1 to 41" to ---claim 1---.


P20453.A01

REMARKS

By the above amendment, the claims have been amended to delete multiple dependency.

If there should be any questions, the Examiner is invited to contact the undersigned at the telephone number listed below.

Respectfully submitted,
Masanori NANBU et al.


Bruce H. Bernstein
Reg. No. 29,027

January 3, 2001
GREENBLUM & BERNSTEIN, P.L.C.
1941 Roland Clarke Place
Reston, VA 20191
(703) 716-1191

-1-

DESCRIPTION

MARKETING SUPPORTING SYSTEM

5 Technical Field

10 The present invention relates to a marketing supporting system. In particular, to a technical field for performing an efficient product proposal, and for implementing instantaneous answer of estimation to various product requirements and order reception input in a marketing place.

Background Art

15 Conventionally, marketing of a product such as a die for machining is performed through marketing activities in which a sales person visits a working factory or the like to conduct business activity, which is so-called door-to-door selling style.

20 In the door-to-door selling, when such a product as a die is proposed to a customer, a sales person merely selects a product(s) from many products through paper catalogs to explain the product(s) therethrough.

25 Also, when a die required by a customer is a die with a special shape which is not a standard die, the sales person brings a die specification drawn on such a sheet as a paper which is required by the customer back to a design department of his/her company. In this design department, design and check of drawings (verification about whether or not the special die can be manufactured)
30 are conducted and the result is notified to the sales

person. The sales person prepares an estimate for the die on the basis of the result and visits the customer again to present the estimate and receive an order of the product. The information about this order reception is input into a database in a head office of the company to issue an instruction to a manufacturing department after he/she comes back to his/her sales station or the like.

In such a process, however, there is a drawback that a product(s) cannot be presented to a customer(s) efficiently. Also, there is another drawback that, when a sales person is asked by a customer, he/she cannot answer the question efficiently.

Furthermore, when a die with a special shape (hereinafter, called special die) is ordered, such an order is brought back to the company and a design and check of drawings are conducted in the design department. For this reason, there is still another drawback that an estimate including an appointed data of delivery cannot be presented to the customer immediately, which results in that a long time is required from an order reception to delivery.

Simultaneously, since a sales person brings back a specification of a special die based upon a handwriting indication, an oral indication or the like to give a person(s) in the design department the specification, there often occurs an error of an original instruction of a customer or misunderstanding of the sales person. For this reason, there occurs claims from customers because manufactured products do not meet

specifications.

Disclosure of Invention

5 The present invention has been made in order to solve the above problems in the conventional art.

An object of the present invention is to present a product to a customer efficiently and in a various manner.

10 Also, another object of the present invention is to answer a customer's question to a product instantaneously and allow sales or marketing activities in a uniform level.

15 Furthermore, still another object of the present invention is to determine whether a standard product requested can be manufactured and whether or not a special shaped product requested can be machined in a door-to-door selling place.

20 Moreover, another object of the present invention is to allow instantaneous estimation and order reception input in a door-to-door selling place.

The summary of a marketing supporting system according to the present invention for solving the above problems is as follows:

25 One feature of the present invention is to provide an increase profit calculating apparatus which can grasp cost consumption easily and can grasp cost reduction easily and rapidly.

The increase profit calculating apparatus comprises:

30 first die screen creating means which creates a first

die apparatus screen (205) for displaying a first die apparatus; and

increase profit screen creating means which is operated in response to a click operation of a specific mark on the first die apparatus screen and which creates an increase profit screen (207) for displaying increase profit occurring by employing the first die apparatus instead of a second die apparatus corresponding to the first die apparatus.

The increase profit screen comprises:

question item fields (207a - 207d) on which a plurality of questions about operations of the first die apparatus and the second die apparatus and relating to costs following the operations are presented;

a field (207i) on which a first total cost is displayed within a predetermined time period due to use of the first die apparatus;

a field (207j) on which a second total cost is displayed within the predetermined time period due to use of the second die apparatus; and

a field (207k) on which an increase profit field for displaying increase profit obtained by employing the first die apparatus is displayed.

Then, the increase profit calculating apparatus is provided with calculating means which calculates the first and second costs and the increase profit according to an answer to the questions from an operator.

According to the above configuration, cost consumption can be grasped easily and cost reduction can be grasped easily and rapidly.

It is preferable that the question items in the increase profit screen (207) includes the number of die apparatus exchanges per one day, a time required for die apparatus exchange per one time, personnel expenses per predetermined time, and the number of working days within a predetermined term.

A second feature of the present invention is to provide a inferiority phenomenon countermeasure guiding apparatus which allows search and selection of an optimal countermeasure to a inferiority phenomenon. The inferiority phenomenon countermeasure guiding apparatus comprises:

inferiority phenomenon screen creating means which creates a inferiority phenomenon screen (209) for displaying a plurality of inferiority phenomena in predetermined kinds of workings such as punching or the like; and

inferiority phenomenon cause screen creating means which is actuated by clicking a inferiority phenomenon display portion in the inferiority phenomenon screen and which creates a inferiority phenomenon cause screen (211) for displaying a list of causes (such as fatigue of a spring, a clearance unsuitableness and the like) causing the inferiority phenomenon.

It is preferable that the inferiority phenomenon countermeasure guiding apparatus further comprises avoidance information screen creating means which is actuated by clicking a portion displaying one cause in the list of causes and which creates an avoidance information screen (213) for displaying information for

avoiding the one cause.

It is preferable that the inferiority phenomenon countermeasure guiding apparatus comprises specific die screen creating means which is actuated by clicking a predetermined portion of the inferiority phenomenon cause screen (211) or a predetermined portion of the avoidance information screen (213) and which creates a specific die screen (217) for displaying a specific die for avoiding the inferiority phenomenon.

According to these structures, it is made possible to search for and select an optimal countermeasure to an inferiority phenomenon easily.

Another feature of the present invention is to provide a inferiority phenomenon countermeasure guiding apparatus for a die for bending machining. This apparatus comprises cause/countermeasure display screen creating means which creates a cause/countermeasure screen (223) for displaying a cause of a inferiority phenomenon in a predetermined kind of workpiece such as bending workpiece or the like and a plurality of countermeasures of a first type for avoiding the inferiority phenomenon due to the cause; and

countermeasure explanation screen creating means which is actuated by clicking a portion displaying one countermeasure in the cause/countermeasure screen and which creates a countermeasure explanation screen (225) for explaining specific contents of the countermeasure through a drawing(s) and a character(s).

This inferiority phenomenon countermeasure guiding apparatus further comprises specific die screen creating

means which is actuated by clicking a predetermined portion of the cause/countermeasure screen or the countermeasure explanation screen and which creates a specific bending die screen (227) for displaying a specific bending die for avoiding the inferiority phenomenon due to the cause.

According to the above structure, it is made possible to select an optimal bending die rapidly when an inferiority phenomenon has occurred in a bending machining.

Another feature of the present invention is to provide a question answer accumulating apparatus comprising means for inputting a question;

means for inputting an answer to the question; and

means for storing the question and the answer in a state mutually correlated with each other.

According to this apparatus, machine operators' questions about dies or the like and answers thereto are accumulated so that knowledge of practically skilled persons responding to the answers are accumulated in a state correlated with the answers and it is possible to respond to a question which will occur in the future easily.

Another feature of the present invention can provide a die retrieval apparatus comprising input screen creating means which creates input screens (231, 233) provided with a field in which a plurality of shapes of a die is input, a field in which the kind of a machine used with the die is input, a field in which a structure of the die is input, and a field in which material for

the die is input; and standard die screen creating means which is actuated by inputting data pieces into the respective fields of the input screens and which, when a die meeting the respective data pieces exists, creates a standard die screen (235) for displaying a sectional configuration of the die, a parts list name, unit prices of respective parts, and, when no die meeting the respective data pieces exists, creates an error display.

According to this apparatus, it is made possible to select a die rapidly by inputting intuitive data pieces such as a die adaptive machine, a die shape or the like when a die is specified by combination of complicated symbols and when it is difficult to describe the combination of the symbols.

Another feature of the present invention is to provide a product automatic designing apparatus (product parameters setting apparatus) which is made possible to perform automatic designing of a die product at a door-to-door selling place or the like easily in answer to even a requirement for a product except for standard products. This product automatic designing apparatus (product parameters setting apparatus) can design a product shape on the basis of shape/material data of a group of products which have been classified and registered based upon the shape patterns of products in response to an estimate requirement for not only standard products on a product catalog but also specially shaped die products which cannot be substituted for standard products. That is, a die product can be designed parametrically by a simple operation of inputting

predetermined size data regarding a selected shape pattern.

The structure for implementing this feature is, for example, a product automatic designing apparatus (product parameters setting apparatus) which comprises

die shape selection screen creating means which creates shape pattern selection screens (237, 239) used for selection of a shape about a die to be designed, and die dimension parameter input screen creating means which is actuated according to selection and input of a specific shape pattern on the die shape selection screen and which creates a die dimension parameter input screen (241) which allows input of dimension parameters of predetermined portions about the selected die shape, wherein

the shape pattern selection screen (237) includes at least a field which allows selection of the kind of a die to be designed and a field which allows selection of a shape pattern regarding the die to be designed;

the die dimension parameter input screen (241) includes at least a shape parameter input field (241b) which displays a dimension parameter input portion required to specify the selected die shape pattern and the shape of the die to be designed and a dimension parameter input field (241c) in which a dimension parameter of the input portion is input; and

the product automatic designing apparatus (product parameter designing apparatus) comprises design means which performs a design according to a correspondence relationship between die shapes which have been

classified on the basis of die shape patterns and stored previously and dimension parameter groups required to specify the shape of the die.

Incidentally, it is preferable that the previously
5 stored shape pattern is stored so as to correspond to a plurality of dimension parameter groups required to specify the die shape belonging to the shape pattern, and

the dimension input screen is further provided with
10 a dimension input pattern selection field which allows selection of one dimension parameter group from the plurality of dimension parameter groups.

Also, it is preferable that the shape pattern
15 selection screen further comprises adapted shape display field which displays one or a plurality of shape sub-patterns contained in shape variation included in the selected shape pattern.

According to this structure, a sales person can design a special shape die parametrically at a
20 door-to-door selling place without such a consciousness that this die is a special shape die. Accordingly, he/she can design the special shape die at the door-to-door selling place without bringing a customer's requirement back to the design department.

25 Another feature of the present invention is to provide a machining possibility calculating apparatus which allows verification of possibility of real machining about the designed die product rapidly and easily.

30 This machining possibility calculating apparatus

verifies whether or not a desired machining can be performed on the designed die product on the basis of shape data/material data about the designed product, material quality data of material to be machined, and the like. Also, the apparatus checks consistency among input dimension parameters.

The structure realizing this feature comprises, for example, die data input means which inputs die data including shape data of a predetermined die specified by the shape pattern and the dimension pattern of a die to be designed, structure data of the die and material quality data;

material data input means which inputs material data including the plate thickness and material quality of a material to be machined which is machined by the die; and

machining verification means which verifies whether or not the die to be designed can be machined on the basis of the input die data and material data.

Incidentally, it is preferable that the machining verification means performs the verification by comparing the resisting pressure of the die which has been obtained according to a strength calculation from the die data and the machining request pressure required for machining performed by the die which has been obtained from the material data with each other.

Furthermore, it is preferable that the machining verification means performs the verification by checking the consistency among the input dimension data pieces.

According to this structure, since suitability

about numerical values of the dimension parameters is checked, a determination about whether or not it is possible to manufacture the designed product actually, namely it is possible to provide the same, can be made
5 instantaneously during a marketing activity. Accordingly, the number of work steps such as preparation of drawing checking, redesigning or the like is reduced.

Another feature of the present invention is to provide an automatic estimate creating apparatus which
10 provides an estimate about the designed and verified product instantaneously at a marketing place.

The automatic estimate creating apparatus which creates an estimate including data necessary to create an estimate of not only price data of a product which
15 has been designed/verified but also price reduction limitation and delivery time limit data.

The structure realizing this feature comprises input means which inputs product data of a product for which an estimate is to be prepared, the number of products,
20 and customer data;

estimate data storage means in which delivery time limit data corresponding to the product and data about price reduction rate to a fixed price of a die product is stored; and

25 detailed estimate information creating means which outputs detailed estimate information on the basis of the input data,

wherein the detailed estimate information output includes deliverable data determined according to the
30 delivery time limit data and an amount obtained by

discount according to the discount rate data.

Incidentally, it is preferable that the product for which the estimate is to be created can be input by specifying the shape and/or material quality of the product.

According to the structure, since product data is displayed in a interlocking manner with design data specified from the shape or the like, it becomes unnecessary to perform complicated search/re-input from a large number of product codes, catalog numbers or the like. Also, it becomes possible to create an estimate including all information necessary for estimate rapidly and easily. Accordingly, an estimate is created instantly at a marketing place so that an early sales commitment can be obtained.

Another feature of the present invention is to provide an order reception information outputting apparatus which allows an instant order reception regarding the estimated product to issue a production instruction.

This order reception information outputting apparatus can secure an order reception to issue a manufacture instruction while presenting the contents of an estimate to a customer at a marketing place, and can make a communication with manufacture schedule information a remote place to output a deliverable data according to the manufacture schedule at this time.

The structure realizing this feature comprises, for example, order reception information screen creating means which displays an order reception information

screen of a product ordered at a marketing place; and
order reception information transmitting means
which is actuated by clicking a specific mark on the order
reception information screen and which transmits the
5 order reception information to a manufacture end.

Incidentally, in addition, it is preferable that
the order reception information outputting apparatus
further comprises delivery data update displaying means
which displays change in delivery data of a product on
10 the order reception information screen on the basis of
data received in response to transmission of the order
reception information.

According to this structure, it is possible to secure
an order reception rapidly and start manufacture at an
15 early time. Accordingly, an early delivery of a product
is made possible.

Incidentally, in the specification of the present
application, the term "sale object" includes products
such as a die apparatus, a machine part, a blade of a
20 machine, a machine or the like, and services such as
maintenance of these products.

Brief Description of Drawings

Fig.1 is a block diagram showing a configuration
25 of a supporting apparatus of the present invention;

Fig.2 is an explanatory diagram of a table of
contents screen displayed on a display screen of the
supporting apparatus of the present invention;

Fig.3 is one example of a product catalog screen
30 displayed on the display apparatus;

Fig.4 is one example of an increase profit screen displaying increase profit displayed on the display screen;

Fig.5 is one example of an inferiority phenomenon screen displayed on the displaying apparatus;

Fig.6 is one example of a inferiority phenomenon cause screen displaying a list of causes generating an inferiority phenomenon shown in Fig.5;

Fig.7 is one example of an avoidance information screen displaying information for avoiding inferiority causes shown in Fig.6;

Fig.8 is one example of an information screen displaying another method for solving the cause shown in Fig.7;

Fig.9 is an explanatory screen for explaining a special die for avoiding the inferiority phenomenon shown in Fig.6;

Fig.10 is one example of a clearance diagnostic test screen serving as a reference value screen displayed on the displaying apparatus by clicking a predetermined portion on the screen shown in Fig.6 in a case that the cause in Fig.6 is a clearance unsuitableness;

Fig.11 is an accompanying disadvantage and the like display screen which is displayed by clicking a predetermined portion on the screen shown in Fig.10, for displaying an accompanying inferiority phenomenon or disadvantage due to the clearance unsuitableness;

Fig.12 is a cause/countermeasure screen which is displayed by clicking a display portion of the characters "BENDING" on the screen in Fig.2, for displaying a cause

of an inferiority phenomenon in a bending machining and a plurality of countermeasures for avoiding the inferiority phenomenon;

Fig.13 is a screen for explaining the details of a predetermined countermeasure in Fig.12;

Fig.14 is a bending die display screen (special bending die screen) which is displayed by clicking a predetermined portion on the screen in Fig.12 or Fig.13, for explaining a countermeasure bending die (or novel bending die);

Fig.15 is a special bending die detail explanatory screen which is displayed by clicking a predetermined portion on the screen in Fig.14, for explaining the details of suitable material for the countermeasure bending die (novel bending die), a suitable apparatus, functions and the like;

Fig.16 is an explanatory diagram of a die list screen showing a list of punching dies/bending dies and a die data input screen in which data of standard dies is input;

Fig.17 is an explanatory diagram of a second die data input screen for selecting a standard die in punching dies;

Fig.18 is an explanatory diagram of a second die data input screen for selecting a standard die in punching dies;

Fig.19 is an explanatory diagram of a second die data input screen for selecting a standard die in punching dies;

Fig.20 is an explanatory diagram of a parts list screen which is displayed according to a standard die

selection in punching dies;

Fig.21 is an explanatory diagram of a punching die selection screen displaying a list of punching dies and shape patterns;

5 Fig.22 is an explanatory diagram of a punching die selection screen displayed when a predetermined shape pattern is selected in Fig.20;

10 Fig.23 is an explanatory diagram of a dimension parameter input screen displayed in response to selection of the shape pattern of the punching die in Fig.20 and Fig.21;

Fig.24 is an explanatory diagram of a dimension parameter input screen displayed when another dimension parameter group is selected in Fig.22;

15 Fig.25 is an explanatory diagram of a screen showing the result of machining possibility simulation for a punching die manufactured according to input dimension parameters, material and material quality in Fig.23;

20 Fig.26 is an explanatory diagram of a parts list screen displayed in response to a special die selection in punching dies;

Fig.27 is an explanatory diagram of a punch die selection screen displaying a list of bending dies and shape patterns;

25 Fig.28 is an explanatory diagram of a dimension parameter input screen displayed in response to shape pattern selection for a bending die in Fig.26;

30 Fig.29 is an explanatory diagram of a special item input screen displayed in response to special item input selection in Fig.27;

Fig.30 is an explanatory diagram of a screen showing the result of machining possibility simulation for a bending die manufactured according to input dimension parameters, material and material quality;

5 Fig.31 is an explanatory diagram of a screen showing the result of machining possibility simulation of a bending die manufactured according to dimension parameters of different values, material and material quality in Fig.29;

10 Fig.32 is an explanatory diagram of an estimate detail information input screen displayed in response to a die product selection on the parts list screen;

15 Fig.33 is an explanatory diagram of an estimate detail information input screen displayed in response to another die product selection on the parts list screen;

Fig.34 is an explanatory diagram of an example of an estimate output in response to selection of estimate issue on the screen in Fig.31;

20 Fig.35 is an explanatory diagram of an example of a main menu on a portable terminal for sales person according to an embodiment of the present invention;

Fig.36 is an explanatory diagram of a screen for selecting a workpiece shape on the basis of a customer's drawings;

25 Fig.37 is an explanatory diagram of a screen in which workpiece dimensions are input;

Fig.38 is an explanatory diagram of a screen for selecting a die according to workpiece shape/workpiece dimensions;

30 Fig.39 is an explanatory diagram of a screen

indicating additional machining to a selected die on the screen in Fig.38;

Fig.40 is an explanatory diagram of a screen displaying resisting pressure calculation of the die which has been subjected to the additional machining specified in Fig.39;

Fig.41 is an explanatory diagram of a screen displaying a price of the die including the additional machining specified in Fig.39;

Fig.42 is an explanatory diagram of a screen indicating another additional machining to the selected die; and

Fig.43 is an explanatory diagram of a screen displaying resisting pressure calculation of the die which has been subjected to the additional machining specified in Fig.42.

Best Mode for Carrying out the Invention

An embodiment of the present invention will be explained below with reference to the drawings.

Referring to Fig.1, an embodiment of a marketing supporting apparatus of the present invention comprises a database 105 in which data is

stored, a display apparatus 106, and a communication apparatus 107 performing communication of data with an external apparatus. A marketing supporting apparatus 101 comprises a product proposal supporting section 102, an estimate creating section 103, and an order reception information creating apparatus 104. Then, the product proposal supporting section 102 comprises an increase

profit calculation apparatus 122, an inferiority phenomenon countermeasure guiding apparatus 123, and a product catalog output apparatus 121. Also, the estimate creating section 103 comprises a product automatic
5 designing apparatus (product parameter setting apparatus) (die retrieval apparatus) 132, a machining possibility calculation apparatus 133, and an estimate information output apparatus 131. Also, the product database 105 comprises a standard product database 105
10 in which data about standard dies is stored, a pattern special die database 152 in which special dies patterned are stored, and a non-patterned special die database 153 in which extremely special dies which cannot be patterned are stored.

15 For the marketing supporting apparatus 101 in the present embodiment, a program performing processing explained below is created and a computer system which can execute this processing by loading this created program is used. This computer system includes a
20 so-called general purpose machine, a workstation, a PC, a NC (Network Computer) or the like. In the present invention, however, it is preferable that a portable type PC which can be carried to a marketing place. The hardware configuration of the computer system used in the present
25 embodiment is provided with a CPU for performing various processings, a memory such as a program memory/data memory or the like, an external storage apparatus such as a FD, a CD or the like, and an output apparatus such as a display unit or the like. The processings explained below can
30 be performed as off-line processings in a single PC

without connection to a computer in a head office or a branch office except for processings which are performed in the order reception information creating apparatus 104.

5 Incidentally, the program for implementing the marketing supporting apparatus of the present embodiment is can be saved in one of various recording media such as a magnetic disk, an optical disk, a memory card and the like. The present embodiment can be implemented by
10 reading recording medium into the program memory to execute the program.

Next, processing contents of the marketing supporting apparatus according to the embodiment of the present invention will be explained.

15 When the supporting apparatus is actuated, a contents table screen 200 shown in Fig.2 is displayed on the display apparatus 106 (hereinafter, a case that the term "displayed" is merely used means that "display" is performed on the display apparatus 106 when there is
20 no special explanation). Displayed on this contents table screen are a product introduction field 201, a various phenomena countermeasure (namely, inferiority phenomena countermeasure) field 203, and a question answer field 204. Incidentally, sub-fields of a punching
25 field 203a and a bending (curving) field 203b are displayed on the various phenomena countermeasure field 203.

In the above, for example, when a display portion of the product introduction field 201 is clicked, the
30 product catalog output apparatus 121 is actuated, and

a product introduction screen 205 (a first die apparatus screen) as shown in Fig.3 is displayed. In Fig.3, as one example, triple holders holding three dies are displayed. According to this holder, once the holder is set on a punch press, punching machining of three kinds corresponding to the three dies mounted on the holder can be performed without exchanging dies.

According to the supporting apparatus of this invention, increase profit obtained by using the triple holder can easily be calculated. That is, when a predetermined portion on the display screen 205 in Fig.3 is clicked, an increase profit screen 207 displayed in Fig.4 is displayed. The increase profit screen 207 displays increase profit occurring by employing a triple holder instead of a single holder holding only one die. That is, displayed on this screen 207 are a question 207a for asking the number of holder exchanges per day, a question 207b for asking an exchanging time required per one time, a question 207c for asking labor cost of a worker per one hour, and a question 207 for asking working days per one month. Answer fields 207e, 207f, 207g and 207h in which an operator inputs answers to these questions are provided. That is, the field 207e in which an answer to the question 207a is input, the field 207f in which an answer to the question 207b is input, the field 207g in which an answer to the question 207c is input, and the field 207h in which an answer to the question 207d are provided. Then, when an operator writes answers in these fields, a labor cost (one month) required for holder exchanges occurring when a single holder is used is

displayed on a field 207i, a labor cost per one month corresponding to a case of use of a triple holder is displayed on a field 207j, and increase profit per one month occurring when a triple holder is used instead of a single holder is displayed on a field 207k.

According to the invention, regarding to the triple holder (the first die apparatus), increase of profit obtained by the use of the triple holder instead of the single holder is calculated easily. In other words, the cost waste made by the use of the single holder (the second die apparatus) is grasped easily, and so is the cost reduction by the use of the triple holder (the first die apparatus).

Next, when a field of the punching 203a in the various phenomena countermeasures 203 is clicked on the contents table screen 200 shown in Fig.2, the various phenomena countermeasure guiding apparatus (inferiority phenomena countermeasure guiding apparatus) 123 is actuated and an inferiority phenomena screen 209 shown in Fig.5 is displayed on the display apparatus 106. Images 209a, 209b, 209c and the like displaying various inferiority phenomena in a punching machining are displayed on the screen 209. Then, for example, when a display portion of a stripping error 209b is clicked on the screen 209, the inferiority phenomena cause screen creating means is actuated, and an inferiority phenomena cause screen 211 displaying a plurality of causes generating the stripping error (inferiority phenomenon) is displayed on the display apparatus 106 (Fig.6). Incidentally, the stripping error means that a workpiece bites a tip portion

of a punch which has performed punching machining and a portion of the workpiece which has been subjected to the punching machining is brought up according to elevation of the tip portion of the punch.

5 As shown in Fig.6, punch blade tip melt adhesion 211a, lubricant unsuitableness 221b, clearance unsuitableness 211c, wear 211d, spring fatigue 211e and the like which may be causes of the stripping error are displayed on the screen 211. Also, a simulation
10 displaying a situation where the stripping error occurs as an animation together with the plurality of causes 211a to 211e is displayed on a simulation display section 211g.

Accordingly, a drawback which has occurred in the
15 material to be machined can easily be grasped and understood as a stripping error in punching machining by referring to this simulation screen. Also, since the causes of the stripping error are listed up on the screen 211, the cause of the inferiority phenomenon can easily
20 be grasped and understood by referring to the list and a countermeasure to the inferiority phenomenon can be proposed.

An avoidance information screen 213 displaying a method (information) for avoiding this cause is displayed
25 by clicking a display portion of one cause in the cause list (Fig. 7). In this embodiment, for example, when a display portion 211e of the spring fatigue (cause) is clicked, a spring fatigue avoidance information screen 213 shown in Fig.7 is displayed. For example, such
30 information that it is necessary to exchange springs

periodically in order to avoid the spring fatigue is displayed on this screen 213. In detail, information 213a that it is necessary to perform exchange for each two years when pressure of 1.2 tons or less is applied (corresponding to 1,000,000 hits), it is necessary to perform exchange for each year when pressure of 1.2 tons to 3.2 tons is applied (corresponding to 500,000 hits), and it is necessary to perform exchange for each half a year when pressure of 3.2 tons to 6 tons is applied (corresponding to 200,000 hits) is displayed as criteria for exchange.

Therefore, according to the apparatus of the present invention and the above screens, when a stripping error occurs and its cause is considered to be spring fatigue, the necessity that spring exchange is performed periodically at predetermined intervals in order to avoid such an error is understood so that efficiency can be improved in machining.

When a predetermined portion is clicked on the screen 213 shown in Fig. 7, a screen 215 shown in Fig. 8 is displayed. A countermeasure performed on a current die to reduce the number of exchanges of the die in possible range and avoid the spring fatigue is displayed on this screen 215. In this embodiment, for example, information 215a showing necessities of increase in die size and increase in spring force is displayed. Also, as problems occurring due to use of such a die, information 215b about increase in cost of a die, necessity of change of the program, or lack in the number of turret stations is also displayed on the screen 215.

Accordingly, by referring to these information items 215a, 215b, it can easily be understood that the increase in size of the die and the increase in spring force can be applied to avoid the spring fatigue which is the problem but such problems as increase in cost of a die, necessity of program change, lack in the number of stations and the like occur.

Then, when a countermeasure product 211f or 211h shown in Fig.6, or a field 213b of Fig.7 or a field 215c of Fig.8 is clicked, a screen 217 shown in Fig.9 is displayed on the display apparatus 106. In this screen 217, information 217 about a gas spring is displayed as a die for avoiding the stripping error. In particular, a sectional configuration of the gas spring is displayed at a portion indicated by reference numeral 217b. This gas spring uses a apparatus where gas is sealed instead of a mechanical spring in order to urge a punch body 217e and a punch head 217f of a punch die upward against a punch guide 217b.

Displayed on the screen 217 is also a graph 217c showing that the pressure of the gas spring is larger than that of the mechanical spring in a region where a stripping error is easy to occur. Furthermore, displayed on the screen 217 is information 217d about preferable functions or effects obtained by a punch die of the gas spring.

Therefore, according to this screen 217, the structure of the gas spring type die, the advantages of the gas spring compared with a standard coil spring and the preferable functions of the gas spring can be

understood and grasped at once. Also, a determination can be made about whether or not a gas spring type die should be employed as a countermeasure to the current inferiority phenomenon in punching machining easily and rapidly while profitability is taken in consideration.

Incidentally, when an explanation field 217e is clicked on the screen 217, an animation where the punch body 217e and the punch head 217f are moved up and down relative to the punch guide 217b is displayed in a simulation manner on the field 217d, and sound for explaining the structure and operation functions of the gas spring die is output from a predetermined sound apparatus. Thereby, the structure, the functions and the operations of the gas spring can be understood more easily.

On the screen 211 shown in Fig. 6, when unsuitableness of an clearance size formed between an inner diameter of a die and an outer diameter of a punch chip is considered as a cause of a stripping error, a display portion 211 of clearance unsuitableness is clicked on the screen 211. Thereby, reference value screen creating means is actuated so that a clearance diagnosis test screen 219 is displayed as a screen displaying a reference value (Fig. 10). In this embodiment, a question field 219a for asking machined material to be used for machining, a question field 219b for asking the thickness of the material, and a question field 219c for asking a clearance in the machining are provided on the screen 219. When an operator inserts answers to these questions, a determination is made about whether the clearance value

219f is too small, suitable or too large in view of the values 219d and 219e of the machined material quality and the thickness of the machined material. On this screen 219, it is displayed in a reference value display field 219g that a standard value of a clearance to the machined material quality 219d and the thickness 219e is 0.3 mm, and a display 219h showing that a value 219f of the clearance is small as compared with the reference value is displayed.

Next, when a display portion 219i relating to the display 210h is clicked, a screen 221 is displayed on the display apparatus (Fig.11). This screen 221 is an accompanying disadvantage display screen 221 displaying other inferiority phenomena or disadvantages which may occur when the clearance is below the suitable clearance. In detail, description 221d is displayed on the screen 221 that, when the current clearance is smaller than the suitable clearance, the secondary shear occurs so that a large load applied to a punch and die. Also, a description 221a is displayed that according to advance of wear in a punch and a die, cost in consumption increases and the working ratio is lowered. Furthermore, a description 221b is displayed that product inferiority occurs, loss in material occurs and loss in machining charge occurs. Also, a description 221c "twice or more decrease in cost can be realized by selecting a die for each material/plate thickness" is displayed.

Accordingly, referring to the screen 221, it is understood that, when the current clearance is smaller than a suitable clearance, various disadvantages or

inferiority phenomena occur, and it is understood that the double or more decrease in cost can be achieved by using dies having different hole diameters for respective materials or plate thicknesses. Thereby, it is understood that it is important to set a clearance to a suitable value in order to achieve rapidness of machining or accurate machining and for attaining decrease in cost. As a result, by referring to this, a suitable clearance can be achieved, accuracy in machining can be improved, working ratio can be increased, and decrease in cost can be attained.

Incidentally, displayed on the screen 219 (Fig.10) is information 219j that, when the clearance is larger than a suitable clearance, "deformation of material becomes large prior to start of cutting, which results in the same as a case that the die has been consumed". Thereby, it is understood that a drawback occurs even when the clearance is too large, and importance of selecting a clearance suitably is understood.

Therefore, by referring to these screens, a clearance can be selected suitably, and accuracy in machining, rapidness in machining or decrease in cost can be achieved.

Referring to Fig.2 again, when a bending field 203b for various phenomena countermeasure is selected, a screen 223 shown in Fig.12 is displayed in the display apparatus. This screen 223 is a cause/countermeasure screen showing bending flaw occurrence of various inferiority phenomena and a plurality of countermeasures (a first kind of countermeasures) for avoiding the bending

flaw occurrence. Incidentally, the bending flaw means a flaw occurring at a machined portion of a material indicated by each arrow of an explanation diagram 223a on the screen 223. As the countermeasures to the bending flaw, application of oil to a shoulder portion of a die (223b), attachment of a tape to a die (223c), application of clamping state bending (223d), application of vinyl-coating (223e) and the like are displayed on the screen 223. Incidentally, regarding these countermeasures, their features and directions corresponding to these countermeasures are also displayed, respectively (223f, 223g). Also, besides the specific countermeasures, general countermeasures for avoiding bending flaw occurrence are displayed in a field 223h on the screen 223. Especially, as the third countermeasure of the general countermeasures, setting of proper V width to required tons is displayed.

Accordingly, by referring to these displays, it can be understood easily that when bending flaw occurs, what is considered as its cause, or which countermeasures can be employed to the cause (general countermeasures and specific countermeasures). Therefore, one or a plurality of these countermeasures can be employed to minimize bending flaw occurrence in a bending machining.

For example, when a display portion 223b of countermeasure 1 is clicked, a screen 225 shown in Fig. 13 is displayed. Displayed on this screen 225 is a specific operation "apply oil to a shoulder portion of a die" through a drawing (225a).

Accordingly, by referring to a display 225a on the

screen 225, a specific content or specific operation of each countermeasure 1 can easily be understood through a drawing or characters.

Next, when a countermeasure product display portion 223i or 225b on the screen 223 or the screen 225 is clicked, a screen 227 is displayed on the display apparatus (Fig.14). This screen 227 is a specific bending die screen showing that a new type die named "Selatic Die" can be used in order to prevent the bending flaw from occurring. Formed on the screen 227 is a display 227b that a suitable material capable of using the Selatic Die is stainless steel, iron or the like as well as a display 227a of features of the Selatic Die.

When a display 227c displaying a shape of the Selatic Die through a drawing is clicked on the screen 227, a screen 229 is displayed on the display apparatus (Fig.15). More specific functions, suitable materials or suitable apparatus are explained on the screen 229 in detail, as shown in Fig.15.

Accordingly, by referring to the screens 227 and 229, a new die for bending flaw countermeasure can be evaluated easily and rapidly, so that the problem about the bending flaw can be rapidly solved.

Referring to Fig.2 again, when the display portion 205 of Question and Answer is clicked on the screen 200, the past questions and the answers thereto are displayed in a mutually related state. By referring to these, an operator can refer to the past questions relating to the operations, functions, movements of the die and, when there is any questions relating to the current problem,

he/she selects these questions so that he/she can easily obtain the answer about the current outstanding problem of the die by referring to the answers displayed relating to the respective questions. Then, when the question about the currently relating problem cannot be obtained from a list of the questions accumulated in the past, these questions are input by the question input means. Thereby, these questions are transmitted to a master supporting apparatus for supporting apparatus via a proper communication means 107, and a practically skilled answerer who operates this master supporting apparatus inputs answers to these questions into the master supporting apparatus. Thereby, these answers are transmitted from the master supporting apparatus to the supporting apparatus of the present invention, and they are stored a proper storage apparatus in this supporting apparatus. Accordingly, the current outstanding problem can be solved by utilizing this answer. Also, by storing the answer from this master supporting apparatus in a state relating to the question, an operator can refer to this question and this answer when a question similar thereto will occur, so that he/she can solve a problem which will occur in the future easily and rapidly. Incidentally, regarding a new question, when an operator operating this supporting apparatus can answer the question, the operator inputs the answer into the supporting apparatus at the place. Thereby, the answer is stored in the storage means of the supporting apparatus in a state where it is related to the question.

When a die required by a customer is a standard one,

the supporting apparatus of the present invention also serves as a die retrieval apparatus for selecting the required die easily and rapidly. That is, when a die is specified with a complicated combinations of symbols and it is difficult to remember the combination of symbols, the die retrieval apparatus can select a standard die easily and rapidly by inputting intuitive data such as a machine suitable for use of a die, the shape of a die or the like.

This die retrieval apparatus is provided with input screen creating means which creates input screens 231, 233 which includes a field in which a plurality of shapes of a die is input, a field in which the kind of a machine using a die is input, a field in which the structure of a die is input, and a field in which material quality of a die is input. The input screen is displayed, for example, as a first input screen 231 shown in Fig.16. Regarding, for example, a punching machining die, a list field 231a which classifies trimming dies or forming dies on this screen 231. When a standard die field 231b of the trimming dies is selected from the list field 231a, a sectional configuration of this standard die is displayed on a shape field 231c. In this embodiment, a circle, square, oval, rectangle, WD shape, SD shape, center punch, standard burring are displayed as standard shapes. Incidentally, in this embodiment, the term "standard shape" denotes the shape determined with two parameters. When a selection button 231d is pushed in a state shown in Fig.16, the selection condition input screen 233 serving as a second input screen is displayed

(Fig.17, Fig.18 and Fig.19). Displayed on this selection condition input screen 233 are a field 233a in which the kind of a machine in which a die is used is input, a field 233b in which a holder size of a die is input, a field 233c in which the structure of a punch of the dies is input, a field 233d in which material quality of the punch is input, a field 233e in which the structure of the die is input, and a field 233f in which the material quality of the die is input.

Accordingly, when predetermined data is input into the respective fields 233a to 233f, whether or not a standard die meeting these conditions exists is retrieved in the supporting apparatus of the present invention. When the standard die exists, a standard die screen 235 as shown in Fig.20 is created. Displayed on this standard die screen 235 are a sectional configuration field 235a showing a sectional configuration of a die attached with numbers specifying parts, and a part name unit price field 235b displaying the name and the unit price of each part displayed on the sectional configuration field 235a.

Accordingly, by referring to the screen 235, a price for each part in a standard die and a name of the part can be grasped easily. That is, according to the apparatus of the present invention, even when the complicated symbols for specifying the kind of a die is forgotten, it is possible to specify the die and obtain information about the price for each part in the die easily.

Incidentally, an error indication is displayed on the screen 231 or 233, when a die which does not exist

is specified.

Next, functions of a marketing supporting apparatus according to the present embodiment performed when a required product does not exist in standard dies will be explained with reference to Fig.21 to Fig.31.

Incidentally, in the followings, the commercial article mainly denotes a standard product. When the article is merely called product, it denotes a standard product and a special shape product.

In this case, the marketing supporting apparatus according to the present embodiment serves as an automatic designing apparatus.

(1) One example where, when a required product is a punching die, it is a punch which is used for punching machining will be explained.

When selection and input is performed by clicking a predetermined punch kind from die kinds 237a on a shape pattern selection screen 37 shown in Fig.21 (which is merely called "clicked"), a die shape pattern selection screen creating means is actuated, and the die shape pattern selection screen creating means displays a plurality of shapes according to the selected kind on a shape display field 237c in a linkage manner. Incidentally, in a case of a punching die, the shape pattern to be displayed shows a trimming hole shape formed by the punching die.

In Fig.21, according to selection of a special shape 237b for performing trimming, corresponding shapes are displayed in a field 237c. When one pattern among the displayed trimming hole shape patterns is clicked and

a selection field 237d is clicked, die size parameter input screen creating means is actuated. Next, the die size parameter input screen creating means displays a size parameter input screen 241 (Fig.23) about the selected trimming shape pattern.

The product automatic designing apparatus (product parameter setting apparatus)132 in this embodiment achieves automatic designing by retrieving the database 105. Shape data, material data, and commercial article data which are classified on the basis of shape patterns are stored in a corresponding manner in the database 105. Data of a product group corresponding to the shape patterns is divided to standard product database 151, pattern special shape (non-standard product to which a shape pattern is applicable) database 152, and non-pattern special shape (non-standard product to which a shape pattern is not applicable) database which are then stored in respective memory regions.

Incidentally, as shown on the screen 239 (Fig.22), various patterns, namely, adaptive shapes 239c, which can obtain a specific shape by performing shape change on the basis of the selected trimming shape pattern in a stage where a predetermined shape pattern has been clicked on the shape pattern selection screen 237. Accordingly, a confirmation can easily be made about which trimming hole shape pattern the required special shape die belongs to.

Fig.23 shows a die size input/output screen 241 for inputting size parameters corresponding to the shape pattern selected on the screen 237.

A figure 241b of the selected trimming hole shape pattern is displayed on the screen while size parameters to be input for specifying a shape is displayed on a shape pattern in a corresponding manner. Reference symbols
5 A, B, K, R and S are size parameters required for specifying a trimming hole shape. While referring to the figure display 241b, required sizes are input into size parameter input field 241c. Here, when the size parameters are input, the trimming hole shape portion of the figure in
10 the figure display 241b is changed in shape according to the input parameter values. Also, enlargement or reduction (241l) or positioning (241m) of the figure display 241b can be performed optionally. The displayed figure can be printed (241n).

15 Also, the size parameters shown about the shape pattern which is the size input screen 241 are registered as a plurality of combinations thereof in advance, and the respective combinations are limited to the minimum number of combinations required for specifying a shape
20 which includes sizes. For this reason, it is made possible to specify the required special shape die by input of the minimum number of parameter according to the size data specified by a customer. As shown in a size input pattern display field 241a, the first parameter
25 combination among 8 pattern-registered size parameter combinations which have been registered has been displayed in Fig. 23. In order to input size parameters of a different combination, such an operation may be employed that a next size pattern screen is displayed
30 by clicking an ordinary next screen or an entire screen

calling field. It is shown in a size input pattern display field 243b on the size input screen 243 in Fig.24 that the current pattern is the third size input pattern.

Incidentally, data pieces required for specifying die products except for the dies for trimming hole shapes are respectively shown in a commercial article code field 241e, a holder size field 241f showing a aperture of a holder supporting a die, and structure fields/material quality fields 241g to 241j of a punch or a die. The display contents of these fields include data which has been input in advance on the commercial article selection conditions input screen 233 (Fig.18).

According to the above procedure, a shape including respective size parameters, a commercial article code, structure, material quality, holder size are specified, so that a design about a special shape die which is not included in standard products is completed.

Accordingly, a die specification required through a hand-written drawing(s) and the like is selected from trimming shape patterns defined preliminarily, and the selected trimming hole shape pattern is shape-changed by applying specific size parameters thereto, so that a desired trimming hole shape can be specified.

(2) A case where a required product is a bending die.

Next, an example where a required product is a bending die used for bending machining will be explained. In the case of the bending die, reference shapes of respective standard products are stored as shape patterns, and a die shape meeting a required product specification

can be obtained by shifting the selected shape patterns.

When a predetermined bending kind is clicked from die kinds 249a on a bending shape pattern selection screen 249 shown in Fig.27, die shape pattern selection screen creating means is actuated. The die shape pattern selection screen creating means displays a plurality of shape patterns of bending dies on a shape display field 249c in an interlocking manner according to the selected kind.

In Fig.27, according to selection of a goose neck shape 249b, a corresponding shape patterns are displayed in a field 249c. When one pattern is clicked among the displayed goose neck shape patterns and selection field is clicked, a die size parameter input screen creating means is actuated. Next, the die size parameter input screen creating means displays a size specific input/output screen 251 (Fig.28) about the selected goose neck shape pattern.

Incidentally, on the screen 249 (Fig.27), various patterns, namely, adaptive shapes 249e, which can obtain a specific shape by performing shape-change on the basis of the selected goose neck shape pattern in a stage where a predetermined shape pattern 249d has been clicked on the shape pattern selection screen 249 can be displayed.

Accordingly, a confirmation can easily be made about which goose neck shape pattern the required special shape die belongs to. Incidentally, as shown in Fig.27, in the case of the bending dies, respective shape patterns correspond to specific commercial article codes and catalog numbers on a catalog. Accordingly, a stage where

this shape pattern has been selected means that size parameters (including an angle) about a main portion has been specified. In Fig.27, numeral 453 in the selected shape pattern 249d displays upper three figures of a catalog number to which the shape pattern belongs.

Fig.28 shows a die shape specifying screen 251 in which size parameters are input according to the shape pattern selected on the screen 249.

A figure 251b of the selected goose neck shape pattern and a divided ear shape are displayed on the screen 251 with size parameter values for specifying the goose neck shape displayed on the shape pattern. An angle at a tip end portion used for bending is shown as 88° which is a predetermined value. Meanwhile, as for a tip end R (roundness of a tip end portion of a bending die), a plurality of selectable parameter values, namely 0.2, 0.6, 0.8, 1.5 and 3.0, are displayed for the shape pattern.

While referring to this figure data 251b, a desired tip end value is input into a tip end R input field 251c.

According to the above procedure, a shape including respective size parameters, a commercial article code, a catalog number, (and a structure, material quality and the like specified by the commercial article code and the catalog number) are specified, so that designing of a standard product and a special shape die which is not covered with standard products are completed.

Here, shape change is performed on the goose neck shape of the display 251a so that a goose neck shape of a special shape can be obtained. In this case, a special mention item field 251d shown in Fig.28 is clicked. In

response to this click, the shape specifying screen creating means is actuated. The shape specifying screen creating means displays a special mention item selection screen 253 (Fig. 29). A commercial article code and catalog number 253a of the selected shape pattern is displayed on the special mention item selection screen 253 together with a corresponding commercial article name 253a. Special specification items which are applicable to the selected shape pattern are recited on an applicable special mention item field 253c. In Fig. 29, for example, when a customer specifying mark 253d is selected, it is copied to an application special mention item field 253g so that special mention items to be applied can be grasped easily.

Also, regarding the selected shape pattern, an additional machining item field 253e accompanying shape change is displayed on the special mention item selection screen 253. Adjustment or the like of a tip end angle, a tip end R, a special ear shape, a product recess is made selectable using the additional machining item field 253e. Here, when a tip end angle change 253f is selected, the shape specifying screen creating means further displays a tip end angle change screen 255 (Fig. 30).

In Fig. 30, the selected goose neck shape pattern is displayed as figure data 255a while size parameters of portions capable of being additionally machined are shown. The current parameter values of a tip end angle (K) and the tip end R (R) which are changeable size parameter are displayed in a size input field 255c. A special shape bending die can be designed by replacing

the displayed parameter values with desired parameter values. The shape of the figure data 255a is also changed and displayed in an interlocking manner with the replacement of the parameter values.

5 According to the above procedure, a shape including respective size parameters, a commercial article code, a structure and material quality are specified so that designing of a special bending die which is not covered with standard products is completed.

10 Accordingly, a die specification required through a hand-written figure(s) or the like is selected from predetermined bending shape patterns without consciousness about whether the die is a standard product or it is a special shape product, and size parameters
15 necessary for additional machining are applied to the selected bending shape pattern so that a desired bending shape can be specified by shape-changing the bending shape pattern.

Next, functions of the marketing supporting
20 apparatus according to the present embodiment which verifies whether or not a product which has been designed according to the automatic designing apparatus can be machined will be explained with reference to Fig.21 to Fig.31.

25 In this case, the marketing supporting apparatus according to this embodiment functions as a machining possibility calculating apparatus.

(1) In a case of a punching die, first of all, one
30 example where a punching die has been designed will be explained. The thickness and material quality of a

workpiece to be machined are input into the machined material input field 243d on the above-mentioned input screen, for example, 243 (Fig.24). As shown in Fig.25, here, a clearance value 245f, the clearance being formed between an outer diameter of a punch and an inner diameter of a die, and the total number of shots 245g are further input, and the machining possibility field 245b is clicked. Material data input means actuated by this click delivers data of material to be machined to machining verification means according to input of the data of material to be machined.

Meanwhile, as shown in Fig.24, according to input of a commercial article code 243e of a punch, a holder size 243f, structure and material quality 243g to 243i of a punch/a die, the die data input means delivers this shape data to the machining verification means. Incidentally, as the data pieces shown in 243e to 243i, data pieces which have been already input through input into the above-mentioned commercial article condition input screen have been displayed.

The machining verification means first performs verification about whether or not the design shape can be machined on the basis of these machined material data and die data. Specifically, the machining possibility means performs this verification by comparing resisting pressure obtained by strength calculation from die data of the selected die (shape data/structure data/material quality data) and machining requiring pressure required for punching workpiece on a specified material which is required from material data (plate thickness and material

quality) with each other.

The machining verification means checks consistency about whether or not the size parameters applied to the shape pattern constitute a trimming hole shape.

In Fig.25, the results of these verifications is displayed as a message "capable of machining" on a message field 245c.

Accordingly, determination about whether or not the die which has been designed in the automatic designing apparatus is a die which can bear an actual machining can be grasped simultaneously with the design of the die.

(2) Case of a bending die

Next, one example where a bending die has been designed will be explained. The plate thickness 255f and the material quality 255g of a workpiece to be machined are input into the machined material input field on, for example, the field 255 of the above-mentioned die shape specifying input screen (Fig.30). Material data input means actuated by clicking the machining possibility field 255b delivers data of the material to be machined to the machining verification means according to input of these data pieces of material to be machined.

Meanwhile, as shown in Fig.30, when respective size data, material quality data, structure data and a tip end angle or a tip end R of the shape pattern of the bending have been corrected, the die data input means delivers the die data to the machining verification means according to input of the corrected size data.

Also, as shown in Fig.30, in the case of the bending

die, the V width of the die is further input. Since this V width has been registered in advance as a default value, when input of the width is omitted, the default value is used as the V width. The V width data is also delivered to the machining verification means as a part of the die data. The machining verification means performs verification similar to the case (1) of the punching die on the basis of these material data and die data.

As shown on a machining possibility verification screen 255 (Fig.30), the verification result about machining possibility "resisting pressure: 45 ton/m and machining requiring pressure: 51 ton/m (calculation as V width = 48 mm) is displayed in the message field 255j. Simultaneously, an alarm message "resisting pressure lack" is displayed on the message field 255k to call an operator's attention.

Accordingly, a determination about whether or not the bending die which has been designed in the automatic designing apparatus is a die which can bear an actual machining can be grasped by the display of the verification result simultaneously with the designing.

Next, functions of the marketing supporting apparatus according to this embodiment which creates estimate information of a product which has been designed by the automatic designing apparatus and has been verified by the machining possibility calculating apparatus will be explained with reference to Fig.26 to Fig.34.

In this case, the marketing supporting apparatus according to the embodiment functions as an estimate information outputting apparatus.

As shown on the parts list screen 247 (Fig.26), parts relating to a punch to be estimated are displayed on a parts display field 247a by selection of the shape pattern and input of the size parameters as described in Fig.22 to Fig.25 without directly inputting a commercial article code, a catalog number and the like. Purchase unit of the die product which has been designed and verified is displayed on a parts list display field 247b so as to correspond to the display of parts.

When a predetermined purchase unit is selected by clicking on this parts list field 247b, detail estimate information creating means is actuated. This detail estimate information creating means reflects and displays the commercial article data of the selected die product on an estimate list field 259c of the estimate detail screen 259 shown in Fig.32.

Like the above, regarding the bending die, as shown on the parts list screen 251 (Fig.28), when a predetermined purchase unit is selected by clicking on this parts list field 251b, detail estimate information creating means is actuated. This detail estimate information creating means reflects and displays the commercial article data of the selected die product on an estimate list field 259c of the estimate detail screen 259 shown in Fig.32.

Fig.32 is the estimate detail screen 259 in this embodiment. The commercial article data such as a commercial article code of a die product selected from each list, a catalog number, quantity, shape, a commercial product name and the like is displayed on the estimate

list field 259c. When a calculation button 259m is clicked on the estimate detail screen 259, the estimate of each die product displayed in the list is displayed.

Price data and delivery time data about each die product to be estimated can be confirmed on the estimate detail screen 259. For example, it is assumed that, for example, a die product of a catalog number 45302E has been pointed in the second line of the estimate list field 259c. Regarding the pointed die product, unit cost 259g, price 259p, discount rate 259k, discount amount 259l and the like are displayed as price data together with a commercial article name 259f. This discount rate 259k is a value which has been set in advance for each customer and for each product (each product group). The discount amount 259l is calculated on the basis of the discount rate 259k and the product unit cost 259g, and an estimate amount is displayed as a value obtained by subtracting the discount amount 259l from the product unit cost 259g. At this time, it is possible to select application of a variable discount rate set for each customer or application of a fixed discount rate.

Simultaneously, a reference delivery time 259h, a deliverable day 259i, a customer request delivery day 259j and the like are displayed as delivery time data.

As for the reference delivery time, a value (necessary days) which has been set preliminarily for each product (each product group) is displayed with a specific delivery time code in a corresponding manner.

Day obtained by decoding this delivery time code to the number of necessary days to add the same to the

current date is displayed on the deliverable day 259i.

When an estimate issue button 259n is clicked on the detail estimate screen 259, information on the detail estimate screen 259 is output as an estimate 263 of a formal format which can be submitted to a customer (Fig.34). As shown in Fig.34, an offered price 263i to which a total discount amount 263h applied to the estimated die product is applied can be presented. Incidentally, the estimate can be output not only to a printer connected to the marketing supporting apparatus according to the embodiment but also to a facsimile provided on a place specified by a fax output indication button 261i (Fig.33).

Accordingly, it is made possible to input a die product to be estimated easily and rapidly by specifying commercial article data from the shape pattern and the size parameters without directly inputting a commercial article code or a catalog number. Incidentally, in this time, it is a matter of course that input contents of the shape and size parameters (shape data) which have been input by the design and verification are stored and corresponding commercial article data can be input in an interlocking manner with the input means for estimate information on the basis of the stored shape data.

Also, discount data and delivery time data necessary to present an estimate is stored in advance and the estimate is prepared using these data pieces so that an instant response of a required die product can be performed.

Finally, the marketing supporting apparatus

according to this embodiment which outputs and transmits order reception information according to the prepared estimate information of a product will be explained.

5 In this case, the marketing supporting apparatus according to the embodiment functions as an order reception information creating apparatus.

When a customer indicates his/her intention of purchase on the estimate detail screen 259 shown in Fig.32 or in response to the output result of this estimate detail
10 information, an order reception decision button 259o is clicked on the estimate detail screen 259.

Order reception information to which an order reception number has been given and which including the contents of the estimate information is prepared by
15 clicking this order reception decision button 259o. Here, a sales person connects a predetermined portable communication equipment 107 (Fig.1) to the marketing supporting apparatus according to the embodiment, and he/she online-transmits/reflects the order reception
20 information to a head office database such as order reception database/manufacture database (not shown) or the like through the portable communication equipment 107. The order reception database in the head office is updated by the transmission of the order reception
25 information, and simultaneously a manufacture instruction can be transmitted to a manufacture department having the manufacture database at real time to instruct manufacture start.

The manufacture schedule and the delivery schedule
30 about the order-received die product are stored in the

manufacture database in the head office. For this reason, the marketing supporting apparatus according to the embodiment can obtain deliverable day as return data to transmission of the order reception information in view of an actual schedule about the order-received die product.

After transmission of the order reception information, it is possible to output an order acknowledgment through a printer, a facsimile or the like to provide it to a customer by clicking a predetermined button on the screen in Fig.32.

Meanwhile, in a case that the marketing supporting apparatus according to the embodiment is used off line, after a sales person returns back to a sales branch or the like, he/she may reflect this order reception information to the head office database such as order reception database/manufacture database or the like.

Accordingly, it is made possible to decide an order reception rapidly and start manufacture early. That is, the order-received die product can be delivered early.

Incidentally, Fig.35 is an explanatory diagram of an example of a main menu 265 on a portable terminal for a sales person according to the embodiment of the present invention. A series of processings of the above marketing support belongs to a consultant 265d and an estimate 265e in a day processing menu 265b on the main menu. Besides the processings for the above-mentioned sales support, processings necessary for morning, day (daytime), and evening according to a timetable of one day of a sales person, respectively can be timely called

from one main menu 265 to be processed.

Fig.36 to Fig.43 show another embodiment of the machining possibility calculating apparatus.

In this case, a bending die is selected on the basis of a workpiece shape. For this reason, as shown in Fig.36, first, a display 270a is clicked on a left field on a workpiece selection screen 270. Thereby, selection branches 270b are displayed on a right field on the screen 270. Here, for example, a workpiece shape 270c is selected on the basis of an order drawing from a customer.

Then, as shown in Fig.37, a workpiece size input screen 272 is displayed on the display apparatus. While referring to a workpiece shape 272a on a right field, desired numerals are input into a size field 272b on a left field. At this time, a size guide display 272c is displayed on the right field in an aspect accompanying the workpiece shape 272a. Accordingly, input of sizes of the workpiece can easily be performed. Thereafter, for example, a standard die 272e is selected from a die selection field 272d.

As shown in Fig.38, an interference state display screen 274 showing an interference state between the workpiece shape 272 and the standard die shape 274a is displayed. As shown in Fig.38, when the standard die 274a interferes with the workpiece, another standard die 274b is selected from the die selection field 274 displayed simultaneously. Thereby, while referring to the interference between a workpiece and a selected die, an optimal die can be selected easily.

When there is no die that does not interfere with

the workpiece in standard dies included in the die selection field 272d, a die 276a which does not interfere with the workpiece so much is selected from the standard dies of the die selection field 272d and it is additionally machined (Fig.39). In this case, as shown in Fig.39, after the minimum interference die 276a is selected, an additional machining & resisting pressure calculation field 276b is clicked.

Thereby, as shown in Fig.40, an additional machining specifying screen 278 is displayed. A position and an amount of additional machining are input in an additional machining specifying field 278a on this screen 278. Thereby, a locus of an additional machining is displayed on a screen displaying the die 276a and the workpiece 272a. Accordingly, according to this apparatus, the position/amount of additional machining can easily be determined while referring to the screen. When input of the position/amount of the additional machining is completed, a calculation about whether a die which has been machined additionally can be used is made simultaneously, and the calculation result is displayed on a left field 278c on the screen 278. Accordingly, a determination about possibility of the additional machining is made easily.

According to the above, when the additional machining is determined to be performed and an amount reference field 278d is clicked, a price display screen 280 shown in Fig.41 is displayed. A die price input field 280a and an additional machining price input field 280b are included on this price display screen 280. Therefore,

according to this apparatus, a price of the final die including the additional machining cost can easily be confirmed.

Fig.42 and Fig.43 show a case that, when the additional machining is performed on an appropriate standard die 274a, the die has been made unusable as a result.

In this case, when a proper amount of additional machining is input into an additional machining specifying field 282a of an additional machining specifying screen 282 and an additional machining performing field b is clicked, an additional machining result screen 284 shown in Fig.43 is displayed. A reason that the die which has been subjected to additional machining is unusable is displayed in an impossible reason display field 284a on this screen 284.

Incidentally, the screens 270, 272, 274, 276, 278, 280, 282, and 284 are respectively created by respective screen creating means for creating each screen.

Incidentally, the present invention is not limited to the above embodiments, but it may be modified in various manners without departing from the scope of the present invention.

Industrial Applicability

As explained above, according to the present invention, the following effects can be attained.

That is, functions for retrieving/displaying a product to be proposed are provided through various approaches such as increase profit calculation, a problem

solving die or the like from many product groups. For this reason, efficient and various product proposal activities can be employed.

Also, the present invention provides functions for
5 storing shape patterns and corresponding size parameters of products relating to product data to perform automatic designing/drawing checking/estimating in an interlocking manner. For this reason, it is made possible to propose an estimate about not only standard
10 products but also special shape products instantaneously without returning back to a head office and perform early order reception/early delivery.

In this manner, using the present invention, it is made possible to improve marketing productivity in both
15 stages of commercial article proposal and preparation of estimate and to shorten product delivery time and reduce marketing costs.

-55-
CLAIMS

1. An increase profit calculating apparatus,
comprising:

5 first marketing object screen creating means which
creates a first marketing object screen (205) for
displaying a first marketing object; and

increase profit screen creating means which is
operated in response to a click operation of a specific
10 mark on the first marketing object screen (205) and which
creates an increase profit screen (207) for displaying
increase profit by employing the first marketing object
instead of a second marketing object corresponding to
the first marketing object,

15 the increase profit screen (207) comprising:
question item fields (207a - 207d) which issues a
plurality of questions about works relating to the first
marketing object and the second marketing object and costs
for the works;

20 a field (207i) which displays a first total cost
due to use of the first marketing object within a
predetermined period;

a field (207j) which displays a second total cost
due to use of the second marketing object within the
25 predetermined period; and

a field (207k) which displays increase profit
obtained by employing the first marketing object instead
of the second marketing object,

30 wherein the increase profit calculating apparatus
is provided with calculating means which calculates the

first and second total costs, and the increase profit according to answers to the questions from an operator.

2. An increase profit calculating apparatus
5 according to claim 1, wherein the marketing object includes a product such as a die apparatus, a mechanical part, a blade of a machine tool, a machine tool or the like, or service such as maintenance for the product.

10 3. An increase profit calculating apparatus according to claim 1, wherein the plurality of questions relating to the first marketing object and the second marketing object include a question about the number of works within a predetermined period, and a question about
15 a time required for one time work.

4. An increase profit calculating apparatus according to claim 1, wherein the marketing object is a die apparatus, and the question item includes one of
20 a question group about the number of die apparatus operations per day, a die apparatus operation time per one time, a labor cost per predetermined time, and working days within a predetermined term;

a question group about personnel or mechanical
25 idling time caused by inferiority machining occurring due to use of a second die, labor cost within a predetermined time, and working days within a predetermined term; and

a question group about total working time within
30 a predetermined term in a case that predetermined

machining is performed using the second die, total working time within a predetermined term in a case that the same machining is performed using a first die, labor cost per predetermined time, and working days within a predetermined term.

5. An inferiority phenomena countermeasure guiding apparatus comprises: inferiority phenomena screen creating means which creates an inferiority phenomena screen (209) for displaying a plurality of inferiority phenomena in machining using a marketing object; and inferiority phenomena cause screen creating means which is actuated by clicking a display portion of one inferiority phenomenon on the inferiority phenomena screen (209) to create an inferiority phenomena cause screen (211) for displaying causes of the one inferiority phenomenon.

6. An inferiority phenomena countermeasure guiding apparatus according to claim 5, wherein the inferiority phenomena cause screen (211) displays a list of the causes.

7. An inferiority phenomena countermeasure guiding apparatus according to claim 5, wherein the marketing object is a punching die, and the causes of inferiority phenomenon are spring fatigue, clearance unsuitableness and the like.

8. An inferiority phenomena countermeasure guiding

apparatus according to claim 6, further comprising avoidance information screen creating means which is actuated by clicking a display portion of one cause in a list of the causes to create an avoidance information screen (213) for displaying information for avoiding the cause.

9. An inferiority phenomena countermeasure guiding apparatus according to claim 8, comprising new product screen creating means which is actuated by clicking a predetermined portion of the inferiority phenomena cause screen (211) or the avoidance information screen (213) to create a new product screen (217) for displaying a new product for avoiding the inferiority phenomenon.

10. An inferiority phenomena countermeasure guiding apparatus according to claim 5, further comprising reference value screen creating means which is actuated by, when one cause in the inferiority phenomena cause list is offset from a reference value of a predetermined parameter, clicking a display portion of the cause on the inferiority phenomena cause screen (211) to create a reference value screen (219) for displaying the reference value.

11. An inferiority phenomena countermeasure guiding apparatus according to claim 6, wherein a question field about characteristics of material for defining the reference value is provided on the reference value screen (219).

12. An inferiority phenomena countermeasure guiding apparatus according to claim 11, wherein the characteristics of material are material quality and plate thickness of a material.

13. An inferiority phenomena countermeasure guiding apparatus according to claim 12, wherein a question field about the current value of the parameter is provided on the reference value screen (219).

14. An inferiority phenomena countermeasure guiding apparatus according to claim 10, further comprising accompanying disadvantage screen creating means which is actuated by clicking a predetermined portion on the reference value screen (219) to create an accompanying disadvantage display screen (221) for displaying other inferiority phenomena or disadvantages which may occur due to the cause.

15. An inferiority phenomena countermeasure guiding apparatus, comprising cause/countermeasure screen creating means which creates a cause/countermeasure screen (223) which displays a cause of an inferiority phenomenon in machining using a marketing object and a plurality of a first kind of countermeasures for avoiding the inferiority phenomenon due to the cause; and

countermeasure explanation screen creating means which is actuated by clicking a display portion of one

countermeasure on the cause/countermeasure screen to create a countermeasure explanation screen (225) for explaining specific contents of the countermeasure.

5 16. An inferiority phenomena countermeasure guiding apparatus according to claim 15, wherein the marketing object is a die for bending.

10 17. An inferiority phenomena countermeasure guiding apparatus according to claim 15, comprising new product screen creating means which is actuated by clicking a predetermined portion on the cause/countermeasure screen (223) or the countermeasure explanation screen (225) to create a new product screen (227) for displaying a new product for avoiding the inferiority phenomenon due to the cause.

15 18. An inferiority phenomena countermeasure guiding apparatus according to claim 17, further comprising new product detail screen creating means which is actuated by clicking a predetermined portion on the new product screen (227) to create a new product detail screen (229) for displaying detail explanation such as suitable material/suitable apparatus/function or the like of the new product.

20 19. A question-answer accumulating apparatus comprising:

 means which inputs a question about a marketing
30 object;

means which inputs an answer to the question; and
means which stores the question and the answer in
a mutually related manner.

5 20. A die retrieval apparatus comprising:

die data input screen creating means which creates
die data input screens (231, 233) provided with a
plurality of fields in which features of a marketing
object are input; and

10 standard die screen creating means which is actuated
by inputting data items into respective fields on the
input screens (231, 233) and which, when a marketing
object corresponding to the respective data items exists,
creates a standard die screen (235) for displaying a price
15 relating to the marketing object and, when no marketing
object corresponding to the respective data items exists,
creates an error indication.

21. A die retrieval apparatus according to claim
20, wherein the plurality of fields in which features
of a marketing object are input include a field (231a)
in which a shape of the marketing object is input, a field
(233a) in which the kind of a machine in which the marketing
object can be used is input, fields (233c, 233e) in which
25 the structure of the marketing object is input, and fields
(233d, 233f) in which the material quality of the
marketing object is input.

22. A die retrieval apparatus according to claim
30 21, wherein a part list name of the marketing object and

a price of each part are displayed on the standard die screen (235).

23. A product parameter setting apparatus
5 comprising:

marketing object shape selection screen creating means which creates shape pattern selection screens (237, 239) for selecting a shape relating to a marketing object to be set with parameters; and

10 marketing object size parameter input screen creating means which is actuated according to selection and input of a specific shape pattern on the marketing object shape selection screens to create a marketing object size parameter input screen (241) in which size
15 parameters of predetermined portions about the selected marketing object shape.

24. An apparatus according to claim 23, wherein the shape parameter selection screens (237, 239) includes
20 a field (237a) for selecting the kind of the marketing object to be set with parameters and a field (237c) for allowing a shape pattern relating to the marketing object to be set with parameters.

25 25. A product parameter setting apparatus according to claim 24, wherein the marketing object size parameter input screen (241) comprises

a shape pattern display field (241b) which displays the selected marketing object shape pattern and a size
30 parameter input portion necessary for specifying the

shape of the marketing object to be set with parameters,
and

a size parameter input field (241c) which allows
input of size parameters of the input portion.

5

26. A product parameter setting apparatus according
to claim 25, further comprising parameter setting means
which performs parameter setting on marketing object
products which are classified on the basis of shape
patterns of marketing objects, the parameter setting
being performed according to correspondence relationship
between the shapes of the marketing objects which have
been stored in advance and size parameter groups necessary
for specifying the shapes of the marketing objects.

10

15

27. A product parameter setting apparatus according
to claim 26, wherein the shape pattern is stored so as
to correspond to a plurality of size parameter groups
necessary for specifying the shape of the marketing object
which belongs to the shape pattern, and

20

the marketing object size parameter input screen
(241) includes a size input pattern selection field which
allows selection of one size parameter from the plurality
of size parameter groups.

25

28. A product parameter setting apparatus according
to claim 26 or 27, wherein the shape pattern selection
screens (237, 239) further comprises an application shape
display field (239c) which displays one or plural shape
sub-patterns included in shape variations of the selected

30

shape pattern.

29. A product automatic designing apparatus (product parameter setting apparatus), comprising:

5 marketing object shape pattern selection screen creating means which creates a shape pattern selection screen (237) which allows selection of a trimming hole shape of a marketing object apparatus used for machining of a predetermined kind, such as a punching or the like; and

10 marketing object size parameter input screen creating means which is actuated according to the selection and input of a specific trimming hole shape pattern on the marketing object shape selection screen to create a marketing object size parameter input screen (241) which allows input of size parameters about the trimming hole shape pattern of the selected marketing object, wherein

20 the shape pattern selection screen (237) includes at least a field which allows selection of the kind of a marketing object to be designed (to be set with parameters), and

25 a field which allows selection of the trimming hole shape pattern of the marketing object to be designed (to be set with parameters); and

30 the marketing object size parameter input screen (241) includes at least a shape pattern display field (241b) which display the trimming shape pattern of the selected marketing object and an input portion of size parameters necessary for specifying the trimming hole

shape of the marketing object to be designed (to be set with parameters), and

a size parameter input field (241c) which allows input of size parameters of the input field.

5

30. A product automatic designing apparatus (product parameter setting apparatus), comprising:

marketing object shape pattern selection screen creating means which creates a shape pattern selection screen (249) which allows selection of a shape of a marketing object used for machining of a predetermined kind, such as a bending or the like; and

marketing object size parameter input screen creating means which is actuated according to the selection and input of a specific shape pattern on the marketing object shape selection screen to create a marketing object size parameter input screens (251, 253) which allow input of size parameters about the shape pattern of the selected marketing object, wherein

the shape pattern selection screen (249) includes at least a field (249a) which allows selection of the kind of the marketing object to be designed (to be set with parameters), and

a field which allows selection of the shape pattern relating to the marketing object to be designed (to be set with parameters); and

the marketing object size parameter input screens (251, 253) include at least a shape pattern display field (251a) which displays the selected marketing object shape pattern and main size data of the marketing object shape

30

pattern, and

a size parameter input field which allows shift of the selected shape pattern and input of size parameters for specifying a desired shape.

5

31. A machining possibility calculating apparatus comprising:

marketing object data input means which inputs marketing object data including shape data of a predetermined marketing object specified by a shape pattern and size parameters of a marketing object to be designed, structure data of the marketing object, and material quality data;

10

material data input means which inputs material data including features of material to be machined by the marketing object; and

15

machining verification means which verifies whether or not the marketing object to be designed is capable of being machined on the basis of the input marketing object data and material data.

20

32. A machining possibility calculating apparatus according to claim 31, wherein the features of the material to be machined includes the plate thickness and the material quality of a plate material.

25

33. A machining possibility calculating apparatus according to claim 32, wherein the machining verification means performs the verification by comparing the resisting pressure of the marketing object obtained

30

according to strength calculation from the marketing
object data and machining requiring pressure necessary
for machining which is performed by the marketing object
which has been obtained from the material data with each
5 other.

34. A machining possibility calculating apparatus
according to claim 31 or 33, wherein the machining
verification means performs the verification by checking
10 consistency between the input size data pieces.

35. A machining possibility calculating apparatus
according to any one of claims 31 to 34, wherein, when
the marketing object to be designed is a die for machining
15 of a predetermined kind such as punching or the like,
the marketing object data includes structures and
material qualities of a punch and a die, and a clearance
between the punch and the die.

36. A machining possibility calculating apparatus
according to any one of claims 31 to 34, wherein, when
the marketing object to be designed is a die apparatus
for machining of a predetermined kind such as bending
or the like, the marketing object data further includes
25 a tip end R, a tip end angle of the die, and a V width
of the die.

37. An automatic estimate creating apparatus
comprising:

30 input means which inputs product data to be estimated,

the number of the products and customer data;

estimate data storage means which stores delivery time data corresponding to the product and discount rate data of the product to its price; and

5 detail estimate information creating means which outputs detail estimate information on the basis of the input data, wherein

the detail estimate information to be output includes a deliverable day according to the delivery time data and discount amount according to the discount rate data.

38. An automatic estimate creating apparatus according to claim 37, wherein the product data to be
15 estimated is input by specifying the shape of the product and/or the material quality thereof.

39. An automatic estimate creating apparatus according to claim 37 or 38, wherein the input means
20 further inputs special mention specification data about the input product, and

when the special mention specification is charged, the detail estimate information creating means further adds a price corresponding to the special mention
25 specification to a marketing price of the product and creates estimate information on the basis of a marketing unit price after added.

40. An order reception information creating
30 apparatus comprising:

order reception information screen creating means which displays an order reception information screen of a order-received product at a marketing place; and

- order reception information transmitting means
- 5 which is actuated by clicking a specific mark on the order reception information screen to transmit the order reception to a manufacture end.

41. An order reception information creating
- 10 apparatus according to claim 40, further comprising delivery data update display means which changes a delivery day of a product received in response to the transmission of the order reception according to a manufacture schedule to display the changed delivery day
- 15 on the order reception information screen.

42. A computer readable storage medium which stores a computer program which allows a computer to function as any one of the apparatuses according to claims 1 to
- 20 41.

ABSTRACT

The present invention is provided with an increase
profit calculating apparatus (122) which simulates
5 increase profit according to a commercial article
proposal, an inferiority phenomena countermeasure
guiding apparatus (123) which proposes a commercial
article so as to solve a problem, a commercial article
proposal supporting section (102) having a commercial
10 article catalog output apparatus (121), a commercial
article database (105) having shape/material
quality/commercial article data of product groups
classified on the basis of pattern shapes of products,
a product automatic designing apparatus (product
15 parameter setting apparatus) (132) which designs a
product corresponding to a product specification
required using pattern shape data parametrically, a
machining possibility calculating apparatus (133) which
simulates whether or not a designed product is capable
20 of being machined, an estimate creating section (103)
having an estimate information output apparatus, and an
order reception information creating apparatus (104).

FIG. 1




FIG. 2

200




FIG.3

205

PROPOSAL FOR
PROFIT INCREASE

TRIPLE HOLDER
SEMI-AUTOMATIC
TRIPLE HOLDER


HOME

MENU


TRIPLE HOLDER

- ☐ PUNCHING DIE HOLDER WITH TRIPLE ROLES
- ☐ LIGHT ONE-TOUCH MECHANISM FOR DIE SELECTION OWING TO EMPLOYMENT OF FREE BEARING
- ☐ EASY AND SECURE SHOT PIN SYSTEM FOR DIE POSITIONING


FOR PUNCH SET (PS) DIES



FOR PR DIES



FOR NTC LONG DIES



DIED TO BE USED	SA-64, SA-50, SA-38	1 1/4", 1 1/4", 1 1/4" (1 1/2")	1 1/4", 1 1/4", 1 1/4" (1 1/2")
SLEEVE TO BE USED	SA-32, 38, 50 EACH SLEEVE (OPTION)	1/2"	(STANDARD)
HOLDER INTERIOR LENGTH	450(350)mm	450(350)mm	450mm
OPEN HEIGHT	230mm	244mm	313mm
SHUT HEIGHT	212mm	226mm	295mm
DIE HEIGHT	89mm	89mm	89mm

FIG.4

207

PROPOSAL FOR INCREASE PROFIT TRIPLE HOLDER SEMI-AUTOMATIC TRIPLE HOLDER HOME MENU		TRIPLE HOLDER INCREASE PROFIT 207a (A) NUMBER OF HOLDER EXCHANGES PER ONE DAY? ~ 207b : <input type="text"/> TIMES ~ 207e (B) HOLDER EXCHANGE TIME PER ONE EXCHANGE? : <input type="text"/> 15 MIN. ~ 207f (C) LABOR COST OF WORKING PERSON PER ONE HOUR ? : <input type="text"/> 3000 YEN ~ 207g (D) WORKING DAYS PER ONE MONTH? ~ 207d } 207c : <input type="text"/> 22 DAYS ~ 207h CALCULATION	
		LABOR COST REQUIRED FOR HOLDER EXCHANGE ● SINGLE HOLDER LABOR COST PER ONE HOUR × EXCHANGE TIME PER ONE × NUMBER OF EXCHANGES PER ONE DAY × WORKING DAYS PER ONE MONTH = <input type="text"/> 165,000 YEN	
		● TRIPLE HOLDER 207i HOLDER EXCHANGE TIMES BECOMES 1/3 SINCE BECAUSE THREE DIES CAN BE MOUNTED ON TRIPLE HOLDER LABOR COST PER ONE HOUR × EXCHANGE TIME PER ONE TIME × NUMBER OF 207j EXCHANGES PER ONE DAY × 1/3 × WORKING DAYS PER ONE MONTH = <input type="text"/> 55,000 YEN	
		INCREASE PROFIT PER ONE MONTH = LABOR COST OF CONVENTIONAL SINGLE HOLDER - LABOR COST OF INTRODUCED TRIPLE HOLDER = <input type="text"/> 110,000 YEN RETURN 207k	

FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



10/43

FIG.10





FIG. 11



223




FIG.13

225





FIG.14

IV DIE COUNTERMEASURE COMMERCIAL ARTICLE


COMMERCIAL ARTICLE NAME : SELATIC DIE

FEATURE : LIGHT & INEXPENSIVE

PROPER MATERIAL QUALITY : STAINLESS STEEL, IRON, BONDORIZING THIN PLATE




227a




227b


ACCORDING TO SELECTION OF PICTURE, EXPLANATION IS DISPLAYED ON BLUE FRAME




227c



HARD PLATING



URETHANE SHEET



SELATIC DIE

VARIOUS PROBLEMS IN BENDING MACHINING

IV DIE COUNTERMEASURE COMMERCIAL ARTICLES

2V DIE COUNTERMEASURE COMMERCIAL ARTICLES

OTHER COUNTERMEASURE COMMERCIAL ARTICLES

PROPER V WIDTH & TON NUMBER

HOME PAGE

15/43

FIG.15

229




FIG.16

231a

PUNCHING	BENDING	SET
231b <input type="checkbox"/> TRIMMING {P1} <input type="checkbox"/> STANDARD {Q1} <input type="checkbox"/> SPECIAL SHAPE {Q1}		
231c <input type="checkbox"/> FORMING {P2} <ul style="list-style-type: none"> - BURRING {Q3} - EMBOSING {Q4} - COUNTERSINK {Q5} - DOWELING {Q6} - LOUVRE {Q7} - COUNTERSINK {Q8} - MARKING {Q9} - HALF SHEAR {QA} - KNOCK OUT {QB} 		
231d ADAPTIVE FIGURE <div> ROUND SQUARE SD CENTER PUNCH </div>		
231 <div> SELECTION CLOSE </div>		

FIG. 17




FIG. 18

233

COMMERCIAL ARTICLE SELECTION CONDITION INPUT

SK 233a

NCT

233b

HOLDER SIZE

11/4"

PUNCH

STRUCTURE

STANDARD

MATERIAL QUALITY

SKD

DIE

STRUCTURE

STANDARD

MATERIAL QUALITY

SKD

OK

CANCEL

FIG.19

COMMERCIAL ARTICLE SELECTION CONDITION INPUT

SK

NCT

HOLDER SIZE

11/4"

PUNCH

STRUCTURE

STANDARD

SKD

MATERIAL QUALITY

DIE

STRUCTURE

STANDARD

SKD

MATERIAL QUALITY

OK


CANCEL

FIG.20

235

PARTS LIST

1/1



11/4
AIR BLOW

12.71 ~ 30.0 φ

235a

SPEC. DETAILED FIGURE

No.	ARTICLE NAME	UNIT	PRICE	QUANTITY
01	SET ASSY	XX,XXX		
02	PUNCH ASSY	XX,XXX		
03	PUNCH BODY	XX,XXX		
04	DIE	X,XXX		
05	PUNCH GUIDE	XX,XXX		
06	PUNCH HEAD	X,XXX		

235b

SIZE INPUT

A SIZE

B SIZE

CLEARANCE

DEDICATED KEY

CORNER R

SPECIAL MENTION

SELECTION

CLOSE

FIG. 21

COMMERCIAL ARTICLE SELECTION

PUNCHING BENDING SET

SHAPE FIGURE

I II III IV V VI VII VIII

237b

TRIMMING {P1} 237b

STANDARD {Q1}

SPECIAL SHAPE {Q2}

FORMING {P2}

BURRING {Q3}

EMBOSSING {Q4}

COUNTERSINK {Q5}

DOWELING {Q6}

LOUVRE {Q7}

COUNTERSINK {Q8}

MARKING {Q9}

HALF SHEAR {Q4}

KNOCK OUT {QB}

NON-PATTERN

237c

ADAPTIVE FIGURE

237d

SELECTION

CLOSE

237a

FIG.22




FIG. 23

241b

MACHINING POSSIBILITY

SIZE INPUT PATTERN 1/8

241c

ITEM	VALUE
A	10
B	0
K	0
R	0
S	0
KY	270

241d

MACHINED MATERIAL

PLATE THICKNESS

MATERIAL QUALITY

SPCC

CLEARANCE

241k

MACHINING POSSIBILITY

241e

SK

NCT

HOLDER SIZE

1/2"

241f

PUNCH

STRUCTURE

STANDARD

241g

MATERIAL QUALITY

SKD

241h

DIE

STRUCTURE

STANDARD

241i

MATERIAL QUALITY

SKD

241j

TOTAL SHOTS

241n

FIGURE POSITION

FIGURE PRINT

241m

PRINT

241l

ENLARGEMENT

REDUCTION

241i

UP

CENTER

DOWN

LEFT

RIGHT


FIG.24

243b

MACHINING POSSIBILITY

SIZE INPUT PATTERN

3/8" ☐ ☐ ☐ P102-02



24/43

243c

ITEM	VALUE
B	0
C	0
L	0
R	0
S	0
KY	270

243d

MACHINED MATERIAL

PLATE THICKNESS

MATERIAL QUALITY

CLEARANCE

SK 243e

HOLDER SIZE 243f

PUNCH STRUCTURE 243g

MATERIAL QUALITY 243h

DIE STRUCTURE 243i

MATERIAL QUALITY 243j

TOTAL SHOTS

243k

MACHINING POSSIBILITY

FIGURE SIZE

FIGURE POSITION

FIGURE PRINT

FIG. 25

1000

FIG.26


26/43

247

PARTS LIST

1/1

2" SPECIAL SHAPE



INScribed IN 50.8 ϕ

247a

247b

SPEC. DETAILED FIGURE			
No.	COMMERCIAL NAME	UNIT PRICE	QUANTITY
01	SET ASSY	XX.XXX	
02	PUNCH ASSY	XX.XXX	
03	PUNCH BODY	XX.XXX	
04	DIE	XX.XXX	
05	STRIPPER PLATE	X.XXX	

247c

SPECIAL MENTION

SELECTION

CLOSE

FIG.27

249a

249

COMMERCIAL ARTICLE SELECTION		
PUNCHING	BENDING	SET
<input type="checkbox"/> ONE TOUCH {B1} <input checked="" type="checkbox"/> SK=11- {C0} <input checked="" type="checkbox"/> PUNCH HOLDER {C1} <input checked="" type="checkbox"/> PUNCH {C2} <input type="checkbox"/> STANDARD PUNCH {D8} <input type="checkbox"/> THICK MATERIAL PUNCH {D9} <input type="checkbox"/> GOOSE NECK {H90} ~ 249b <input type="checkbox"/> GOOSE NECK G SERIES <input type="checkbox"/> FRONT RECESS, FR {DC} <input type="checkbox"/> FOR SASH {H70~100} <input type="checkbox"/> POINT PUNCH {H95} <input type="checkbox"/> ACUTE-ANGLED PUNCH {H67~} <input type="checkbox"/> FLATENING PUNCH <input type="checkbox"/> ALP PUNCH {DH} <input type="checkbox"/> R PUNCH {D1} <input type="checkbox"/> HINGE PUNCH {D, <input type="checkbox"/> MIDDLE HAND PUNCH {H8 <input type="checkbox"/> CLOSING PUNCH <input checked="" type="checkbox"/> DIE {C3} <input type="checkbox"/> STEP BENDING/L-SHAPE BENDING {CJ} <input type="checkbox"/> STANDARD {B2} <input type="checkbox"/> SK=10- {C7} <input checked="" type="checkbox"/> PUNCH HOLDER {C8} <input checked="" type="checkbox"/> PUNCH {C9} <input checked="" type="checkbox"/> DIE {CA} <input checked="" type="checkbox"/> MEASURING INSTRUMENT {CG} <input type="checkbox"/> TOOL BOX {CH} <input type="checkbox"/> STEP BENDING/L-SHAPE BENDING {C1} SELECTION FROM WORKPIECE {B3}		
SHAPE FIGURE 249d 		
ADAPTIVE FIGURE ~ 249e <div style="border: 1px solid black; height: 100px; width: 100%;"></div>		
<input type="button" value="SELECTION"/>		<input type="button" value="CLOSE"/>

FIG. 28

251a

PARTS LIST

1/1

NO. 453 TYPE (H90)

No	COMMERCIAL ARTICLE NAME	UNIT PRICE	QUANTITY
1	01 GOOSE PUNCH #453(L)	xxx,xxx	11
1	01 GOOSE PUNCH #453(S)	xx,xxx	
1	01 GOOSE PUNCH #453(DIVISION)	xxx,xxx	

DIVISION
EAR SHAPE

251c

☐ NO TIP END R

☒ TIP END R

251b

251d

FIG. 29

29/43

253

SPECIAL MENTION ITEM SELECTION

253a

COMMERCIAL ARTICLE

253b

ONE TOUCH 88' GOOSE NECK 0.2R L

APPLICABLE SPECIAL MENTION ITEM

253c

001 CUSTOMER SPECIFIED MARK

002 CHECK TABLE ATTACHED

023 CUT SIZE WITHOUT EAR

024 MATCHING OF CUSTOMER DIE HEIGHT

032 DESIGNATION OF RIGHT EAR LENGTH

033 DESIGNATION OF LEFT EAR LENGTH

253d

253e

253f

253g

APPLIED SPECIAL MENTION ITEM

OK

CLOSE

ADDITIONAL MACHINING

TIP END ANGLE/R CHANGE

TIP END ANGLE CHANGE

TIP END R CHANGE


SPECIAL EAR

PRODUCT RECESS

FIG. 30

MACHINING POSSIBILITY

255



TIP END ANGLE CHANGE ~ 255b

ITEM	VALUE
K	80
R	0.2

255c

255d

255e

255f

MACHINED MATERIAL

PLATE THICKNESS

MATERIAL QUALITY

V WIDTH

V WIDTH

SPHC

255h

MACHINING POSSIBILITY

255i

SELECTION

CANCEL

TOTAL SHOTS

1


255j

GUIDANCE: RESISTING PRESSURE IS 45 TON/M AND WORKING REQUIRING PRESSURE IS 52 TON/M
(CALCULATION AS V WIDTH = 48 MM)

WARNING: RESISTING PRESSURE INSUFFICIENT ~ 255k

255j

MACHINING POSSIBILITY



TIP END ANGLE CHANGE ~ 257b

ITEM	VALUE
K	30
R	0.2

257c
257d
257e

MACHINED MATERIAL

PLATE THICKNESS

MATERIAL QUALITY

V WIDTH

V WIDTH

TOTAL SHOTS

257f

257g

257h

CANCEL

ERROR : PLEASE INPUT A VALUE IN RANGE OF $70 \leq K \leq 90$ INTO K SIZE ~ 257j

FIG.31

257

257a

FIG. 32

259

ESTIMATE PARENT NO. A700000		[DELIVERY] (LIMITED COMPANY) A WORKS/ [CONTRACT] (LIMITED COMPANY) A WORKS		259a	
ESTIMATE		ESTIMATE DETAILS		ITEM FOR ORDER RECEPTION	
DISCOUNT RATE		EXCESS APPLICATION		BLANKET DELIVERY	
O APPLICATION		SIMULTANEOUS		CONFIRMATION	
O FIX		TRIAL PUNCHING		FIGURE REQUIRED?	
		STRIP AMOUNT DISPLAY?			
Seq	SK Cat-No.	QUANTITY	SHAPE	COMMERCIAL ARTICLE NAME	A B SIZE SIZE CORNER CLEAR R DEDICATED ESTIMATE AMOUNT
1 11	453021	1	000	ONE TOUCH 88° GOOSE NECK	XX.XXX
2 11	45302E	1	000	No.453 TYPE OF ANGLE, R ADDITIONAL MACHINING	XXX.XXX
TOTAL AMOUNT		XXX.XXX	DISCOUNT AMOUNT	XX.XXX	ESTIMATE AMOUNT XXX.XXX
COMMERCIAL ARTICLE NAME		No.453 TYPE OF ANGLE, R ADDITIONAL MACHINING (B4530KT)			
UNIT PRICE	XXX.XXX	PRICE	SPECIAL MENTION ITEM		
REFERENCE		DELIVERABLE DAY	XXX.XXX	SPECIAL	259c
DELIVERY TIME	5	CUSTOMER REQUEST DAY	1998/06/30	SEQ MENTION ITEM	259n
MARKING No.		DISCOUNT AMOUNT	/ /	VALUE	259o
DISCOUNT RATE	10(%)				
		259p		ORDER RECEPTION DECISION	
		259i		ORDER ACKNOWLEDGMENT	
		259j		FAX	
		259l			
		259m			
		259n			
		259o			
		259p			
		259q			
		259r			
		259s			
		259t			
		259u			
		259v			
		259w			
		259x			
		259y			
		259z			
		259aa			
		259ab			
		259ac			
		259ad			
		259ae			
		259af			
		259ag			
		259ah			
		259ai			
		259aj			
		259ak			
		259al			
		259am			
		259an			
		259ao			
		259ap			
		259aq			
		259ar			
		259as			
		259at			
		259au			
		259av			
		259aw			
		259ax			
		259ay			
		259az			
		259ba			
		259bb			
		259bc			
		259bd			
		259be			
		259bf			
		259bg			
		259bh			
		259bi			
		259bj			
		259bk			
		259bl			
		259bm			
		259bn			
		259bo			
		259bp			
		259bq			
		259br			
		259bs			
		259bt			
		259bu			
		259bv			
		259bw			
		259bx			
		259by			
		259bz			
		259ca			
		259cb			
		259cc			
		259cd			
		259ce			
		259cf			
		259cg			
		259ch			
		259ci			
		259cj			
		259ck			
		259cl			
		259cm			
		259cn			
		259co			
		259cp			
		259cq			
		259cr			
		259cs			
		259ct			
		259cu			
		259cv			
		259cw			
		259cx			
		259cy			
		259cz			
		259da			
		259db			
		259dc			
		259dd			
		259de			
		259df			
		259dg			
		259dh			
		259di			
		259dj			
		259dk			
		259dl			
		259dm			
		259dn			
		259do			
		259dp			
		259dq			
		259dr			
		259ds			
		259dt			
		259du			
		259dv			
		259dw			
		259dx			
		259dy			
		259dz			
		259ea			
		259eb			
		259ec			
		259ed			
		259ee			
		259ef			
		259eg			
		259eh			
		259ei			
		259ej			
		259ek			
		259el			
		259em			
		259en			
		259eo			
		259ep			
		259eq			
		259er			
		259es			
		259et			
		259eu			
		259ev			
		259ew			
		259ex			
		259ey			
		259ez			
		259fa			
		259fb			
		259fc			
		259fd			
		259fe			
		259ff			
		259fg			
		259fh			
		259fi			
		259fj			
		259fk			
		259fl			
		259fm			
		259fn			
		259fo			
		259fp			
		259fq			
		259fr			
		259fs			
		259ft			
		259fu			
		259fv			
		259fw			
		259fx			
		259fy			
		259fz			
		259ga			
		259gb			
		259gc			
		259gd			
		259ge			
		259gf			
		259gg			
		259gh			
		259gi			
		259gj			
		259gk			
		259gl			
		259gm			
		259gn			
		259go			
		259gp			
		259gq			
		259gr			
		259gs			
		259gt			
		259gu			
		259gv			
		259gw			
		259gx			
		259gy			
		259gz			
		259ha			
		259hb			
		259hc			
		259hd			
		259he			
		259hf			
		259hg			
		259hh			
		259hi			
		259hj			
		259hk			
		259hl			
		259hm			
		259hn			
		259ho			
		259hp			
		259hq			
		259hr			
		259hs			
		259ht			
		259hu			
		259hv			
		259hw			
		259hx			
		259hy			
		259hz			
		259ia			
		259ib			
		259ic			
		259id			
		259ie			
		259if			
		259ig			
		259ih			
		259ii			
		259ij			
		259ik			
		259il			
		259im			
		259in			
		259io			
		259ip			
		259iq			
		259ir			
		259is			
		259it			
		259iu			
		259iv			
		259iw			
		259ix			
		259iy			
		259iz			
		259ja			
		259jb			
		259jc			
		259jd			
		259je			
		259jf			
		259jg			
		259jh			
		259ji			
		259jj			
		259jk			
		259jl			
		259jm			
		259jn			
		259jo			
		259jp			
		259jq			
		259jr			
		259js			
		259jt			
		259ju			
		259jv			
		259jw			
		259jx			
		259jy			
		259jz			
		259ka			
		259kb			
		259kc			
		259kd			
		259ke			
		259kf			
		259kg			
		259kh			
		259ki			
		259kj			
		259kk			
		259kl			
		259km			
		259kn			
		259ko			
		259kp			
		259kq			
		259kr			
		259ks			
		259kt			
		259ku			
		259kv			
		259kw			
		259kx			
		259ky			
		259kz			
		259la			
		259lb			
		259lc			
		259ld			
		259le			
		259lf			
		259lg			
		259lh			
		259li			
		259lj			

FIG. 33

261

ESTIMATE PARENT NO. 		[DELIVERY] (LIMITED COMPANY) A WORKS/		261a		ITEM FOR ORDER RECEPTION																																					
ESTIMATE		ESTIMATE DETAILS																																									
<input type="checkbox"/> EXCESS APPLICATION <input type="checkbox"/> SIMULTANEOUS TRIAL PUNCHING		<input type="checkbox"/> MAIL RESPONSE FOR PREPARED HOLE SIZE? <input checked="" type="checkbox"/> STRIP AMOUNT DISPLAY?		<input type="checkbox"/> BLANKET DELIVERY <input type="checkbox"/> CONFIRMATION FIGURE REQUIRED?		<div style="border: 1px solid black; padding: 2px;"> <input type="button" value="INPUT"/> <input type="button" value="DELETE"/> <input type="button" value="CANCEL"/> </div> <div style="border: 1px solid black; padding: 2px;"> COMMERCIAL ARTICLE SELECTION </div> <div style="border: 1px solid black; padding: 2px;"> SIZE CONFIRMATION </div> <div style="border: 1px solid black; padding: 2px;"> COMMERCIAL ARTICLE RETRIEVAL </div> <div style="border: 1px solid black; padding: 2px;"> PAST SALES SEPARATE DIE </div> <div style="border: 1px solid black; padding: 2px;"> CLEAR <input type="button" value="CALCULATION"/> </div>																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Seq</th> <th>SK</th> <th>Cat.No.</th> <th>QUANTITY</th> <th>SHAPE</th> <th>COMMERCIAL ARTICLE NAME</th> <th>A SIZE</th> <th>B SIZE</th> <th>CLEAR</th> <th>CORNER R</th> <th>DEDICATED KEY</th> <th>ESTIMATE AMOUNT</th> </tr> <tr> <td>1</td> <td>10</td> <td>004021</td> <td>1</td> <td>000</td> <td>88° PUNCH 0.2RL</td> <td>20</td> <td>20</td> <td>2</td> <td></td> <td></td> <td>XXX.XXX</td> </tr> <tr> <td>2</td> <td>11</td> <td>322040</td> <td>1</td> <td>002</td> <td>11/4"OH SHAPE</td> <td>20</td> <td>20</td> <td>2</td> <td></td> <td></td> <td>XXX.XXX</td> </tr> </table>		Seq	SK	Cat.No.	QUANTITY	SHAPE	COMMERCIAL ARTICLE NAME	A SIZE	B SIZE	CLEAR	CORNER R	DEDICATED KEY	ESTIMATE AMOUNT	1	10	004021	1	000	88° PUNCH 0.2RL	20	20	2			XXX.XXX	2	11	322040	1	002	11/4"OH SHAPE	20	20	2			XXX.XXX	261b					
Seq	SK	Cat.No.	QUANTITY	SHAPE	COMMERCIAL ARTICLE NAME	A SIZE	B SIZE	CLEAR	CORNER R	DEDICATED KEY	ESTIMATE AMOUNT																																
1	10	004021	1	000	88° PUNCH 0.2RL	20	20	2			XXX.XXX																																
2	11	322040	1	002	11/4"OH SHAPE	20	20	2			XXX.XXX																																
TOTAL AMOUNT XXX.XXX DISCOUNT AMOUNT XX.XXX ESTIMATE AMOUNT XXX.XXX																																											
COMMERCIAL ARTICLE NAME 88° PUNCH 0.2RL		SPECIAL MENTION ITEM <div style="border: 1px solid black; padding: 2px;"> SPECIAL MENTION VALUE SEQ MENTION ITEM </div>																																									
UNIT PRICE XX.XXX REFERENCE 1 ~ 261c DELIVERY TIME DAY MARKING No. CUSTOMER REQUEST DAY DISCOUNT RATE 10(%) DISCOUNT AMOUNT XX.XXX		PRICE DELIVERABLE DAY CUSTOMER REQUEST DAY DISCOUNT AMOUNT																																									
		261d																																									
		261e																																									
		261f																																									
		261g																																									
		261h																																									

34/43

FIG.34

ESTIMATE ~ 263

JUNE 23, 1998

PAGE 1

LIMITED COMPANY A WORKSNo. A700000

REGARDING YOUR INQUIRY OF NO.XXXXXX DATED JUNE 23, WE ESTIMATE
THIS CASE AS FOLLOWS, THEREFORE PLEASE LET US HAVE YOUR ORDER
REGARDING THIS CASE.

263a

263b

DELIVERY TIME AS FOLLOWS

263c

DELIVERY PLACE YOUR DESIGNATED PLACE

TEL
FAX

263d

PAYMENT CONDITION AS USUAL

263e

DELIVERY CONDITION DELIVERY

EFFECTIVE TERM OF ESTIMATE

--	--	--	--

263f

TOTAL AMOUNT ¥ 221,580-					
ITEM	ARTICLE NAME SPEC.	QUANTITY	UNIT PRICE	AMOUNT	DELIVERY TIME
A700045-001	ONE TOUCH 88" GOOSE NECK 0.2R L No.:453021	1	XXX,XXX	XXX,XXX	
A700045-002	ONE TOUCH No.453 TYPE OF ANGLE R ADDITIONAL MACHINIG (B4530KT)	1	XXX,XXX	XXX,XXX	
		1	TOTAL AMOUNT	XXX,XXX	
			YOUR DISCOUNT	XX,XXX	
			PROPOSED PRICE	XXX,XXX	
	- BLANK BELOW -				

263g 263h

263i

FIG.35




FIG. 36

<input type="checkbox"/> PUNCHING <input type="checkbox"/> BENDING <input type="checkbox"/> SET		<input type="checkbox"/> NON-PATTERN	
<div style="display: flex; justify-content: space-between;"> <div> <input type="checkbox"/> ONE TOUCH {B1} -SK=11 - {C0} <input type="checkbox"/> PUNCH HOLDER {C1} <input type="checkbox"/> PUNCH {C2} <input type="checkbox"/> DIE {C3} </div> <div> <input type="checkbox"/> L-STEP BENDING/L-SHAPE BENDING {CJ} -STANDARD {B2} -SK=10 - {C7} <input type="checkbox"/> PUNCH HOLDER {C8} <input type="checkbox"/> PUNCH {C9} <input type="checkbox"/> DIE {CA} </div> <div> <input type="checkbox"/> MEASURING INSTRUMENT {CG} <input type="checkbox"/> TOOL BOX {CH} </div> </div> <div style="margin-top: 10px;"> <input type="checkbox"/> L-STEP BENDING/L-SHAPE BENDING {C1} <div style="background-color: black; color: white; padding: 2px; display: inline-block;">SELECTION FROM WORKPIECE {B3}</div> </div>	<div style="display: flex; justify-content: space-between;"> <div> <input type="checkbox"/> SHAPE FIGURE 1 </div> <div> <input type="checkbox"/> SELECTION OF WORKPIECE SHAPE 270c </div> </div> <div style="margin-top: 10px;"> <input type="checkbox"/> ADAPTIVE FIGURE 270b </div>	<div style="display: flex; justify-content: space-between;"> <div> <input type="checkbox"/> IMAGE INDICATION 270a </div> <div> <input type="checkbox"/> SELECTION CLOSE </div> </div>	


FIG.37

272

GR ES Se CO AR UN RE DE MA

PUNCHING BENDING SET INPUT SIZES NON-PATTERN

ONE TOUCH (R1) SHAPE FIGURE
☒ RETURN BEND CHECK
☐ STANDARD ☒ ONE TOUCH

[WORKPIECE SIZE] 
 PLATE THICKNESS mm
 W SIZE L SIZE
 (WIDTH)=(DEPTH)=
 mm mm mm mm
 mm mm mm mm

ADDITION AND DRAWING

[INPUT PATTERN] CANCEL

[HOLDER TYPE] ☐ Z I ☒ Z II

[DIE] ...PLEASE SELECT 272e
 No.004 (FOR BR RECESS No.1)
 No.004 (FOR BR RECESS No.2)
 ALP (FOR BR RECESS No.3)
 No.117

CLEAR FIGURE

272b

272c

272a

272d

L SIZE (DEPTH)
 W SIZE (WIDTH)

RETURN TO MENU

DETAIL

ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION

×1.0

FIG.38

274


GR ES Se

PUNCHING BENDING SET

ONE TOUCH (R1) SHAPE FIGURE

RETURN BEND CHECK

STANDARD ONE TOUCH

[WORKPIECE SIZE] 

...INPUT

PLATE THICKNESS 1.2 mm

W SIZE L SIZE

(WIDTH)=(DEPTH)=

25 mm 50 mm mm mm

mm mm mm mm

ADDITION AND DRAWING

INPUT PATTERN

CANCEL

[HOLDER TYPE] O Z I O Z II

[DIE] ...PLEASE SELECT

No.004

No.004 (FOR BR RECESS No.1)

No.004 (FOR BR RECESS No.2)

ALP (FOR BR RECESS No.3)

No.117

274b

CLEAR FIGURE

×1.0

272e

272a

274a

67

NON-PATTERN

RETURN TO MENU

DETAIL

ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION

272d

FIG.39


276

GR ES Se CO AR UN RE DE MA

PUNCHING BENDING SET SHAPE FIGURE DIE SELECTION NON-PATTERN

ONE TOUCH (R1)

O STANDARD ☒ ONE TOUCH

[WORKPIECE SIZE] 

...INPUT

PLATE THICKNESS 1.2 mm

W SIZE L SIZE

(WIDTH)= (DEPTH)=

25 mm 50 mm mm mm

mm mm mm mm

[INPUT PATTERN]

W=25.00 L=50.00 F=00 CANCEL

ADDITION AND DRAWING

[HOLDER TYPE] O Z I ☒ Z II 272d

[DIE] ...PLEASE SELECT

No.453

ALP (FOR BR RECESS No.4)

No.045

No.047

No.516

CLEAR FIGURE

X1.0

RETURN TO MENU

DETAIL

ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION

276a

272a

276b

[No.453]

90

FIG.40

278

PUNCHING		BENDING		SET	
[WORKPIECE MATERIAL QUALITY SELECTION]					
TENSILE STRENGTH=28					
[DIE SELECTION]		SPCC <input type="text" value="1.2t"/>			
INWARDLY BENDING RADIUS \div V/6					
O IV DIE		2V DIE			
V WIDTH		<input type="text" value="8"/>			
V ANGLE		<input type="text" value="88°"/>			
<input type="text" value="124(8×12)"/>		<input type="text" value="303 10(8×12)"/>			
[CALCULATION RESULT]					
BENDING TONS = BOTTOMING					
PUNCH WARRANTY		50 ton/m		<input type="text" value="O"/>	
RESISTING PRESSURE		80 ton/m		<input type="text" value="O"/>	
DIE WARRANTY				<input type="text" value="O"/>	
RESISTING PRESSURE				<input type="text" value="O"/>	
BENDING TONS		12.0 ton/m		<input type="text" value="O"/>	
MINIMUM FLANGE LENGTH		5.5mm		<input type="text" value="O"/>	
PUNCH RESISTING PRESSURE		RESISTING PRESSURE OK		<input type="text" value="O"/>	
DIE RESISTING PRESSURE		RESISTING PRESSURE OK		<input type="text" value="O"/>	
DIE WARPING		0.02mm		<input type="text" value="O"/>	
RETURN		REFER TO AMOUNT			

276a

278b

278c

278

272a

278a

X=-19.464

Y=49.598

[No.453]

X1.0

DETAIL

ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION

FIG.41

280

GR	ES	Sc	CO	AR	UN	RE	DE	MA
PUNCHING		BENDING		SET		NON-PATTERN		
ONE TOUCH / P.A.		SHAPE FIGURE						
REFER TO CATNO DECISION & PRICE								
BLADE EDGE ANGLE <input type="radio"/> 88° <input type="radio"/> 90° <input type="radio"/> OTHERS								
LENGTH <input type="radio"/> 835mm(L) <input type="radio"/> 415mm(S) <input type="radio"/> DIVISION								
TIP END R <input type="radio"/> 0.2R <input type="radio"/> 0.6R <input type="radio"/> 0.8R <input type="radio"/> 1.5R <input type="radio"/> 3.0R								
DIE & CATNO GOOSE NECK PUNCH 6mm 453021								
PRICE		280a DIE FEE XXX,XXX ADDITIONAL MACHINING FEE XX,XXX TOTAL XXX,XXX						
RETURN		DECISION		PRINT		X 1.0 $\frac{1}{2}$		
						X=19,464 Y=49,598 [No.453]		
						ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION		

280b

FIG.42

282

GR		ES		Se		CO		AR		UN		RE		DE		MA	
PUNCHING		BENDING		SET		UNSUITABLE DIE SELECTION		NON-PATTERN									
ONE TOUCH (R1)		SHAPE FIGURE															
O STANDARD		ONE TOUCH															
【WORKPIECE SIZE】		◆															
...INPUT		PLATE															
THICKNESS		1.2 mm															
W SIZE		L SIZE															
(WIDTH)=		(DEPTH)=															
25 mm		50 mm		mm		mm		mm		mm		mm		mm		mm	
mm		mm		mm		mm		mm		mm		mm		mm		mm	
【INPUT PATTERN】		CANCEL															
【HOLDER TYPE】		O Z I		O Z II													
【DIE】		...PLEASE SELECT															
No.004																	
No.004 (FOR BR RECESS No.1)																	
No.004 (FOR BR RECESS No.2)																	
ALP (FOR BR RECESS No.3)																	
No.117																	
CLEAR FIGURE		X1.0															
RETURN TO MENU		DETAIL		ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION													

FIG.43

284

GR		ES		Se		CO		AR		UN		RE		DE		MA	
PUNCHING		BENDING		SET		NON-PATTERN											
ADDITIONAL MACHINING JUDGEMENT																	
[WORKPIECE MATERIAL QUALITY SELECTION]																	
[SPCC] 1.2t																	
[DIE SELECTION]																	
INWARDLY BENDING RADIUS $\div V/6$																	
O 1V DIE 2V DIE																	
V WIDTH 8																	
V ANGLE 88°																	
124(8×12)																	
30310(8×12)																	
[CALCULATION RESULT]																	
BENDING TONS = BOTTOMING																	
PUNCH WARRANTY				RESISTING PRESSURE				ton/m									
DIE WARRANTY				RESISTING PRESSURE													
BENDING TONS				MINIMUM FLANGE LENGTH													
PUNCH RESISTING PRESSURE				DIE RESISTING PRESSURE													
DIE WARPING				NOTE: SHORTAGE OF THICKNESS OF UPPER PORTION OF PUNCH													
284a																	
DISPLAY OF REASON FOR IMPOSSIBILITY																	
[No.004] X=-19,464 Y=-49,598																	
x1.0																	
DETAIL																	
ADDITIONAL MACHINING & RESISTING PRESSURE CALCULATION																	

Declaration and Power of Attorney For Utility or Design Patent Application

特許出願宣言書

Japanese Language Declaration

私は、下欄に氏名を記載した発明者として、以下のとおり

宣言する:

私の住所、郵便の宛先および国籍は、下欄に氏名に続いて記載したとおりであり、

名称の発明に関し、請求の範囲に記載した特許を求める主題の本来の、最初にして唯一の発明者である(一人の氏名のみが下欄に記載されている場合)か、もしくは本来の、最初にして共同の発明者である(複数の氏名が下欄に記載されている場合)と信じ、

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

"MARKETING SUPPORTING SYSTEM"

その明細書を

(該当するほうに印を付す)

☐ここに添付する。

☐ _____ 日に出版番号

第 _____ 号として提出し、

_____ 日に補正した。

(該当する場合)

私は、前記のとおり補正した請求の範囲を含む前記明細書の内容を検討し、理解したことを陳述する。

私は、連邦規則典第37部第1章第56条に従い、本題の審査に所要の情報を開示すべき義務を有することを認める。

私は合衆国法典第35部第119条(a-d)項又は第365条(b)項に基づく、下記の外国特許出願又は発明者証出願、或いは第365条(a)項に基づく、少なくとも米国以外の1ヶ国を指名したPCT国際出願の外国優先権利益を主張し、更に優先権の主張に係わる基礎出願の出願日前の出願日を有する外国特許出願、又は発明者証出願或いはPCT国際出願を以下に明記する:

the specification of which

(check one)

☐ is attached hereto.

☒ was filed on July 14, 1999 as

Application No. PCT/JP99/03802

and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119(a-d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the "No" box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed:

Prior foreign applications

先々の外国出願

P 10-200995

(Number)
(番号)

Japan

(Country)
(国名)

July 15, 1998

(Day/Month/Year Filed)
(出願の年月日)

P 10-306057

(Number)
(番号)

Japan

(Country)
(国名)

October 27, 1998

(Day/Month/Year Filed)
(出願の年月日)

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)
(出願の年月日)

Priority claimed

優先権の主張

☒ Yes ☐ No

あり なし

☒ Yes ☐ No

あり なし

☐ Yes ☐ No

あり なし

Japanese Language Utility or Design Patent Application Declaration

☐ その他の外国特許出願番号は別紙の追補優先権欄にて記載する。

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto.

私は、合衆国法典第35部第119条(c)項に基づき、下記の合衆国仮特許出願の利益を主張する。

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

(Number)
(番号) (Day/Month/Year Filed)
出願の年月日

(Number)
(番号) (Day/Month/Year Filed)
出願の年月日

(Number)
(番号) (Day/Month/Year Filed)
出願の年月日

☐ その他の合衆国仮特許出願番号は別紙の追補優先権欄にて記載する。

☐ Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

私は、合衆国法典第35部第120条に基づき下記の合衆国特許出願、又は第365条(c)項に基づく合衆国を指名したPCT国際出願の利益を主張し、本願の請求の範囲各項に記載の主題が合衆国法典第35部第112条第1項規定の範囲で、先の合衆国特許出願又はPCT国際出願に開示されていない限りにおいて、先の出願の出願日と本願の国内出願日又はPCT国際出願日の間に有効となった連邦規則法典第37部第1章第56条に記載の特許要件に所要の情報を開示すべき義務を有することを認める。

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application No.)
(出願番号)

(Day/Month/Year Filed)
(出願の年月日)

(現況)
(特許済み、係属中 放棄済み)

(Status)
(patented, pending, abandoned)

(Application No.)
(出願番号)

(Day/Month/Year Filed)
(出願の年月日)

(現況)
(特許済み、係属中 放棄済み)

(Status)
(patented, pending, abandoned)

☐ その他の合衆国又は国際特許出願番号は別紙の追補優先権欄にて記載する。

☐ Additional U.S. or international application numbers are listed on a supplemental priority sheet attached hereto.

私は、ここに自己の知識にもとずいて行った陳述がすべて真実であり、自己の有する情報および信ずるところに従って行った陳述が真実であると信じ、さらに故意に虚偽の陳述等を行った場合、合衆国法典第18部第1001条により、罰金もしくは禁錮に処せられるか、またはこれらの刑が併科され、またかかる故意による虚偽による陳述が本願にない本願に対して付与される特許の有効性を損なうことがあることを認識して、以上の陳述を行ったことを宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

私、下記署名者は、ここに記載の米国弁護士または代理人に本出願に關し特許商標庁にて取られるいかなる行為に關して、同米国弁護士または代理人が、私に直接連絡なしに私の外国弁護士或るいは法人代表者からの指示を受け取り、それに従うように委任する。この指示を出す者が変更の場合には、ここに記載の米国弁護士又は代理人にその旨通知される。

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from either his foreign patent agent or corporate representative, if any, as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

Japanese Language Utility or Design Patent Application Declaration

委任状: 私は、下記発明者として、下記に明記された顧客番号を伴う以下の弁護士又は、代理人をここに選任し、本願の手続きを遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。そして全ての通信はこの顧客番号宛に発送される。

顧客番号 7055

現在選任された弁護士は下記の通りである。

Neil F. Greenblum
Bruce H. Bernstein
Roger P. Glass
James L. Rowland
Arnold Turk

POWER OF ATTORNEY: As a named inventor, I hereby appoint the attorney(s) and/or agent(s) associated with the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

CUSTOMER NUMBER 7055

The appointed attorneys presently include:

Reg. No. 28,394
Reg. No. 29,027
Reg. No. 30,841
Reg. No. 32,674
Reg. No. 33,094

(5)

Address: **GREENBLUM & BERNSTEIN, P.L.C.**
1941 ROLAND CLARKE PLACE
RESTON, VA 20191

直接電話連絡先: (名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

GREENBLUM & BERNSTEIN, P.L.C.

(703) 716-1191

唯一のまたは第一の発明者の氏名	Full name of sole or first inventor Masanori NANBU
同発明者の署名	Inventor's signature <i>Masanori Nanbu</i>
住所	Residence Kanagawa, Japan
国籍	Citizenship Japan
郵便の宛先	Post Office Address 2-3-28, Numame, Isehara-shi, Kanagawa 259-1126
	Japan
第2の共同発明者の氏名 (該当する場合)	Full name of second joint inventor, if any Toshio TAMURA
同第2共同発明者の署名	Second inventor's signature <i>Toshio Tamura</i>
住所	Residence Kanagawa, Japan
国籍	Citizenship Japan
郵便の宛先	Post Office Address 253-2, Ikehata, Isehara-shi, Kanagawa, 259-1144
	Japan

(第六またはそれ以降の共同発明者に対しては同様の情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Utility or Design Patent Application Declaration

第三の共同発明者の氏名		Full name of third inventor, if any	
共同発明者の署名	日付	<u>Kohji IWAMOTO</u>	Date
住所		<u>KOHJI IWAMOTO</u>	<u>December 26, 2000</u>
国籍		<u>Residence Kanagawa, Japan</u>	
郵便の宛先		<u>Citizenship Japan</u>	
		<u>Post Office Address C/O AMADA COMPANY, LIMITED</u>	
第四の共同発明者の氏名		200, Ishida, Isehara-shi, Kanagawa, 259-1196 Japan	
共同発明者の署名	日付	Full name of fourth inventor, if any	
住所		<u>Yukio FUKUI</u>	Date
国籍		<u>Fourth Inventor's signature Yukio Fukui</u>	<u>December 26, 2000</u>
郵便の宛先		<u>Residence Kanagawa, Japan</u>	
		<u>Citizenship Japan</u>	
		<u>Post Office Address 6-19, Hibarigaoka, Hadano-shi, Kanagawa 257-0046</u>	
第五の共同発明者の氏名		Japan	
共同発明者の署名	日付	Full name of fifth inventor, if any	
住所		Fifth Inventor's signature	Date
国籍		Residence	
郵便の宛先		Citizenship	
		Post Office Address	
第六の共同発明者の氏名		Full name of sixth inventor, if any	
共同発明者の署名	日付	Sixth Inventor's signature	Date
住所		Residence	
国籍		Citizenship	
郵便の宛先		Post Office Address	

それ以降の共同発明者にたいしても同様な情報
および署名を提供すること。))

(Supply similar information and signature for subsequent joint inventors.)